

NO. OF COPIES RECEIVED		3
DISTRIBUTION		
SANTA FE		1
FILE		1
U.S.G.S.		
LAND	FICE	
OPER	OR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

APR 13 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS O. C. C. ARTESIA, OFFICE		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER WELL. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		5. State Oil & Gas Lease No.
1. Name of Operator Yates Petroleum Corporation		7. Unit Agreement Name
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		8. Farm or Lease Name Cannon "FW"
4. Location of Well UNIT LETTER C 990 FEET FROM THE North LINE AND 2310 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 18S RANGE 26E NMPM.		9. Well No. 1
15. Elevation (Show whether DF, RT, GR, etc.) 3368' GR		10. Field and Pool, or Wildcat Und. Atoka S. A
12. County Eddy		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CEMENT <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

Spudded a 15" hole at 6:00 PM 4-3-76.

TD 406' - Ran 10 joints of 10-3/4" 32.75# J-55 casing (419') set at 406'. Cemented w/200 sacks of Class "C" 4% CaCl. PD 3:30 AM 4-4-76. Cement circulated. WOC 12 hours, drilled cement and reduced hole to 9 1/2" and resumed drilling.

TD 1218' - Ran 31 joints of 7" 20# J-55 casing (1222') set at 1218' w/1-Texas Pattern shoe, 2 centralizers at 1176 and 665', basket at 704'. Cemented w/350 sacks of Incor mix + 150 sacks of Class "C" 2% CaCl. PD 4:15 AM 4-6-76. Cement circulated. WOC and cement dropped, filled hole w/1 yard of Ready-mix. WOC 18 hours, cut off casing, nipples up and tested BOP's to 1000#. OK. Drilled plug and tested casing to 600#. OK. Reduced hole to 6 1/4" and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 4-12-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE APR 14 1976

CONDITIONS OF APPROVAL, IF ANY: