

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND FICE	
OPER FOR	

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

APR 21 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DISTANCE FROM THE SURFACE. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. Name of Operator Yates Petroleum Corporation		5. State Oil & Gas Lease No.
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		7. Unit Agreement Name
4. Location of Well UNIT LETTER M 890 FEET FROM THE South LINE AND 430 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 18S RANGE 26E NMPM.		8. Farm or Lease Name Ryburn "EZ"
15. Elevation (Show whether DF, RT, GR, etc.) 3353' GR		9. Well No. 1
		10. Field, Pool, or Wildcat Und. Atoka (S.A.)
		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASINGS <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Set Prod. csg, Perf., Treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

TD 1775'; PBTD 1734'. Ran 17 joints of 4½" 10.5# H-55 (643') and 27 joints of 5½" 15.5# J-55 (1089') of casing (44 joints 1732') set at 1734'. 7 centralizers at 1690, 1670, 1650, 1630, 1610, and 1590', 1570'. 1-Guide shoe, Cemented w/175 sacks of Class "C" cement. Cement circulated. PD 6:00 PM 4-13-76. WOC and tested to 1000#. OK.

Perforated 1619-1695' as follows w/31 .45" holes: 1st Stage: 1623, 27, 31, 35, 39, 46, 53, 57, 61, 67, 71, 79, 93 (13 holes). Acidized w/3000 gallons of 15% regular acid. 2nd Stage: - 1619, 21, 25, 29, 33, 37, 41, 47½, 51, 55, 59, 62, 65, 69, 72½, 80, 1691, 95' (18 holes). Treated all perforations w/60000 gallons of treated water and 100000# 20-40 sand.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 4-20-76

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE APR 22 1976

CONDITIONS OF APPROVAL, IF ANY: