

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	1 2
U.S.G.S.	
LAND OFFICE	
OPERATOR	7

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

MAY 4 1976

O. C. C.  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Cannon "FW"
9. Well No. 2
10. Field and Pool, or Wildcat Und. Atoka S.A.
12. County Eddy

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation ✓
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER <u>E</u> <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>21</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3402' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 9½" hole at 1:00 PM 4-25-76.

TD 1220' - Ran 30 joints of 7" 20# K-55 ST&C (1223.70') of casing set at 1220' KB. 1-Texas notched shoe, centralizers at 1177 and 688', baskets at 729 and 646'. Cemented by Denton w/350 sacks of Lite 2% CaCl cement.\* PD 4:15 PM 4-27-76. Cement circulated. WOC and cement dropped, filled hole to surface w/3 yards of Ready-mix. WOC 18 hours, nipples up, installed BOP's and tested to 1000#. OK. Reduced hole to 6¼", drilled plug, tested to 600#. OK and resumed drilling.

\* + 150 sacks Class C w/ 2% CC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine Tomlinson</u>	TITLE <u>Geol. Secty</u>	DATE <u>4-30-76</u>
APPROVED BY <u>W.A. Gressett</u>	TITLE <u>SUPERVISOR</u>	DATE <u>MAY 1 1976</u>
CONDITIONS OF APPROVAL, IF ANY:		