| HO, OF COPIES RECEIVED | 1 | | | Form C-103 |
|-----------------------------|----------------|----------------|---|---|
| DISTRIBUTION | | | | Supersedes Old |
| SANTA FE | + | | NEW MEXICO OIL CONSERVATION ROMENTO I VE | C-102 and C-103 |
| FILE | 1 | | REUEIVE | D Effective 1-1-65 |
| U.S.G.S, | 1 | | | 5a. Indicate Type of Lease |
| LAND OFFICE | 1 | | MAY 6 1976 | State Fee XX |
| OPERATOR | 17 | | 0 10/0 | 5. State Oil & Gas Lease No. |
| | | •• | CORRECTED REPORT | |
| (DO NOT USE THIS FO | SU APP | | Y NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. ION FOR PERMIT | |
| I. OIL GAS WELL WEL | | | OTHER- | 7. Unit Agreement Name |
| 2. Name of Operator | | | | 8, Farm or Lease Name |
| Yates Petrol | Leur | n Co | orporation γ | Cannon "FW" |
| 3. Address of Operator | | | | 9, Well No. |
| 207 South 4t | th S | Str | eet - Artesia, NM 88210 | 2 |
| 4. Location of Well | | | | 10. Field and Pool, or Wildcat |
| E | | 2 | 310 North 990 Feet from | Und. Atoka S.A. |
| | | | | |
| West | - | | DN 21 TOWNSHIP 185 RANGE 26E NMPM. | |
| | | | MRAUERAUERAUE | |
| | \overline{U} | \overline{U} | 15. Elevation (Show whether DF, RT, GR, etc.) | 12. County |
| | 711 | $\Pi \Pi$ | 3402' GR | Eddy |
| 16. | Che | ck / | Appropriate Box To Indicate Nature of Notice, Report or Oth | ner Data |
| NOTI | | | - | REPORT OF: |
| | | | | |
| PERFORM REMEDIAL WORK |] | | PLUG AND ABANDON | ALTERING CASING |
| TEMPORARILY ABANDON | | | COMMENCE DRILLING OPNS. | PLUG AND ABANDONMENT |
| PULL OR ALTER CASING | | | Change plans \square casing test and cement Jqb $\overline{\mathbb{X}}$ | |
| | | | OTHER | |
| OTHER | | | | |
| | | | | |
| 17. Describe Proposed or Co | ompiet | ea Op | erations (Clearly state all pertinent details, and give pertinent dates, including | estimated date of starting any proposed |

work) SEE RULE 1103.

Spudded a $9\frac{1}{2}$ " hole at 1:00 PM 4-25-76.

TD 1220' - Ran 30 joints of 7" 20# K-55 ST&C (1223.70') of casing set at 1220'KB. 1-Texas notched shoe, centralizers at 1177 and 688', baskets at 729 and 646'. Cemented by Denton w/350 sacks of Lite 2% CaCl cement, followed w/ 150 sacks of Class "C" 2% CaCl. PD 4:15 PM 4-27-76. Cement circulated. WOC and cement dropped, filled hole to surface w/3 yards of Ready-mix. WOC 18 hours, nippled up, installed BOP's and tested to 1000#. OK. Reduced hole to $6\frac{1}{4}$ " and drilled plug, tested to 600#. OK then resumed drilling.

| 18. I hereby certify that the information above is true and complete to t SIGNED | | 5-5-76 |
|---|------------------------|-----------------|
| APPROVED BY U. A. Aressett TIT CONDITIONS OF APPROVAL, IF ANY: | SUPERVISOR, DISTRICT U | DATE MAY 6 1976 |