

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

5. LEASE DESIGNATION AND SERIAL NO.

LC-060888

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Empire South Deep Unit

8. FARM OR LEASE NAME

Empire South Deep Unit  
Gas Com.

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

South Empire - Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

5-18-29 NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole

2. NAME OF OPERATOR

Amoco Production Company

DEC 9 1976

3. ADDRESS OF OPERATOR

P. O. Drawer "A" Levelland, Texas 79336 O.C.C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FNL and 990' FWL Sec. 5 (Unit D, NW/4 NW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3572.7 GL

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Repair Leak in PXA Well

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TP 11194 P&amp;A 7-22-76

Repair small pressure leak on well which was PXA on 7/22/76. Following work performed on 8/16/76, pulled PXA marker and drilled cement from surface to 15' and tagged cement plug at 2858'. Set CIBP at 2850' and capped w/40 SX Class C cement +2% CACL 2852' - 2749' and spotted 20 SX Class C cement +2% CACL from 50' to surface set PXA marker.

Above procedure was witnessed and okayed by U.S.G.S.

RECEIVED

AUG 23 1976

U. S. GEOLOGICAL SURVEY  
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray W. Cox

R. W. COX

TITLE Administrative Assistant

DATE 8-19-76

(This space for Federal or State office use)

APPROVED BY

Joe J. Lara

TITLE ACTING DISTRICT ENGINEER

DATE DEC 7 1976

CONDITIONS OF APPROVAL, IF ANY:

0+4  
1  
1  
1  
1  
20  
USGS - Art.  
Div  
RE.  
Susp.  
Partners

\*See Instructions on Reverse Side