

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates</u>		Lease <u>Krause GE</u>		Well # <u>1</u>	
Location of Well	Unit <u>23105</u> <u>330W</u>	Section <u>22</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>Byrd & Co.</u>		Type of Equipment <u>Rotary</u>		
☒ witness <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15"</u>	<u>10 7/8"</u>	<u>32</u>		<u>400</u>	<u>cin.</u>
<u>9 1/2"</u>	<u>7"</u>	<u>20</u>		<u>1200</u>	<u>"</u>
<u>6 1/4"</u>	<u>4 1/2 + 5 1/2"</u>	<u>9.5 + 15.5</u>		<u>1800</u>	<u>150</u>
Casing Data:					
Surface <u>31</u> joints of <u>7"</u> inch <u>20</u> # Grade <u>API New K-55</u>					
(Approved) (Rejected)					
Inspected by <u>Lelan Merriam</u> date <u>5-2-76</u>					
Cementing Program					
Size of hole <u>9 1/2"</u> Size of Casing <u>7</u> Sacks cement required <u>500</u>					
Type of Shoe used <u>Texas Bm</u> Float collar used <u>None</u> Btm <u>2</u> jts welded <u>Thread Lock</u>					
TD of hole <u>1210'13</u> Set <u>1196'6L</u> Feet of <u>7"</u> Inch <u>20</u> # Grade <u>K-55</u>					
New-used csg. @ <u>1196'6L</u> with <u>150</u> sacks neat cement around shoe <u>class C 2%cc</u>					
+ <u>350</u> sax <u>class C</u> additives <u>6% G. Isomite</u> <u>6% Flocc</u> <u>2% cc</u>					
Plug down @ <u>9:10</u> (AM) (PM) Date <u>5-2-76</u>					
Cement circulated <u>Bottom Yes</u> No. of Sacks <u>35/50</u>					
Cemented by <u>Denton</u> Witnessed by <u>Lelan Merriam</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>Water 92-205, 210-270, 294-571, 581-664</u>					
<u>1063-1108</u>					

*Seal with flow-
1/2" water 13 11 + 14 65*