

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND	FICE
OPER	OR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Supersedes Old
C-102 and C-103
Effective 1-1-66

RECEIVED

MAY 14 1976

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS. D.C.C.

1. Name of Operator Yates Petroleum Corporation	
2. Address of Operator 207 South 4th Street - Artesia, NM 88210	
3. Location of Well UNIT LETTER L 2310 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 18S RANGE 26E NMPM.	
15. Elevation (Show whether DF, RT, GP, etc.) 3350' GR	

5a. Indicate type of well	Fee <input checked="" type="checkbox"/>
6. State Oil & Gas Conservation Commission	
7. Unit Agreement Name	
8. Name of the well	
Krauss "GE"	
9. Well No.	
1	
10. Field	
Und. Atoka S.A.	
12. County	
Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Set Prod. Csg, Perf, Treat	ALTERING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>
---	--	---	--

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

TD 1745'; PBTD 1732'. - Ran 26 joints of 4½" 10.5# H-55 (744'), 25 joints of 5½" 15.5# J-55 (986') (51 joints 1730') set at 1732'. 9-Centralizers at 1703, 1688, 1673, 1658, 1643, 1628, 1598, 1586' and 1-Guide shoe. Cemented w/175 sacks of Class "C" cement. PD 12:30 PM 5-7-76. WOC and tested to 1000#. OK.

Perforated w/23 .50" holes 1551½-1671' as follows: 1st Stage: 1551½, 63, 87, 91, 95, 1602, 12, 25, 31, 65, 71 (11 holes). Acidized w/3000 gallons of 15% regular acid. 2nd Stage: - 1560, 66, 94, 88, 93, 97, 99, 1604, 22, 28, 62 and 68 (12 holes). Treated all perforations w/60000 gallons of treated water and 100000# 20-40 sand.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine Tomlinson</u>	TITLE <u>Geol. Secty</u>	DATE <u>5-13-76</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>MAY 14 1976</u>
CONDITIONS OF APPROVAL, IF ANY:		