				30-015.0	21799
NO. OF COPIES RECEIVED					
DISTRIBUTION	NEW MEXICO OIL CONSI	N R	orm C+101 evised 14-65		
SANTA FE	. /		FD	A. Indicate Type of i	
FILE	(/	RECEIV		STATE	m [X]
U.S.G.S.	C			5. State Oil & Gas Lea	
LAND OFFICE		APR 27 19	976 ^{1°}	5, State Off & Calls Led	ar NO.
OPERATOR		APRA	k k	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	mmmm
	······································				
APPLICATION FOR	<u> </u>	ΔΗΗΗΗΗΗΗΗΗΗΗ			
1a. Type of Work	ARTESIA, OFFICE			7. Unit Agreement Nan	γ r
DRILL	DEEPEN		BACK		
b. Type of Well				8, Furm or Lease Name	•
	OTHER	SINGLE MU ZONE	ZONE	Krauss "GF	· II
2. Name of Operator		9. Well No.			
Yates Petroleum Co	rporation _*			1	
3. Address of Operator				10, Field and Fool, or Wildcat	
207 South 4th Stre		Und. Atoka	(S.A.)		
4. Location of Well K	LOCATED 2310	Sou	th LINE		
UNIT LETTER					
1650 FEET FROM THE	lest 22	185 RGE. 2	6E NMPM		
AND FEET FROM THE	ann an	MINIMIN I		12. County	HIIIIII
				Eddy 🛛 🚫	
AHHHHHHHH	***************	**********	1111111	mmmm	11111111
$\mathbf{\nabla}$			////////		
<u> </u>	*****	19. Froposed Depth	19A. Fermation	Li, inte	$\mathbf{y} \in \mathbf{r}$. The
		.pprox. 1800	San And	ires Rota	rv
Unnnnnnnnnn	J 21A. Kind & Status Plug. Bond	21B. Drilling Contractor		22. Approx. Date Wo	
21. Elevations (Show whether DF, RT, etc 3334 GR	Blanket	Evrd Drilli	ng Co.		
	BIOIREL	L DYIG DITIT		10 0001 03	<u> </u>
23.	PROPOSED CASING A	ND CEMENT PROGRAM			

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING	DEPTH	SACKS OF CEMENT	EST. TOP
15"	10-3/4"	3217	Approx.	400	Circulate	
95"	7"	20≢ŕ	¥I	1200	Circulate	
6 ¹ 4"	4 ¹ ₂ &5 ¹ ₂ "	10.5&15.5#	* *	1800	150 sacks	

It is our intention to drill a San Andres Test. Approximately 400' of surface casing will be run, if needed, to shut off gravel and cavings, intermediate casing will be set 100' below the Artesian zone w/cement circulated. If production is encountered a tapered string of $5\frac{1}{2}$ " and $4\frac{1}{2}$ " production casing will be run, perforated and treated for production.

Mud Program: - FW Gel and LCM to 1200'. Fresh water to TD.

BOP Program: - BOP's will be installed on 7" casing and tested daily FOR 90 DAYS UNLESS DRILLING COMMENCED,

EXPIRES 2-28-76

Ŧ

IN ABOVE SPACE DESCRIBE PROPOSED PRO TIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF I hereby certify that the information above is tru	ARY.			
Signed Christine Josel		Geol. Secty		4-26-76
(This space for State Use) APPROVED BY M. G. Mess	et TITLE	SUPERVISOR, DISTRICT	П ДАТЕ	APR 28 1976
CONDITIONS OF APPROVAL, IF ANY:	Cement must be circulated to surface behind $\frac{10^{-7}}{4^{-7}}$ casing		Notify N.M.O.C.C. in sufficient time to witness cementing the <u>Z</u> "casing	