

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
N.M. CO. COPY
SUBMIT IN TRIPL. (For instructions on reverse side)
RECEIVED
JUN 29 1976Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

New Mexico 0924

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Alscott

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T-18-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Hondo Drilling Company

3. ADDRESS OF OPERATOR

Drawer 2516, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1650' from North Line and 1980' from East Line,
Section 31, T-18-S, R-29-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3421' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

May 13, 1976 to June 10, 1976 - Drilling 7-7/8" hole total depth of 11,311 feet. Well circulated, mixing mud, running logs and conditioned hole to run 5 1/2" casing.

June 13, 1976 at 11:00 A.M. Commenced running 11,316 feet of 5 1/2" OD N-80 Casing; 810 feet of 20 lb. and 10,506 feet of 17 lb. casing, set at total depth of 11,311 feet, cemented with 700 sacks Class H cement with 3/4 of 1% CFR-2 and 8 lbs. salt, 500 gal. mud flush. Plug pumped down with 3% KCL water. Plug down at 9:30 P.M. 6-13-76.

June 14, 1976 at 7:00 A.M. Cement Temperature survey, top of cement at 8475 feet. Plug back total depth 11,238 feet.

June 15, 1976 at 8:00 A.M. Casing and wellhead assembly was tested to 3000 lbs. without pressure drop prior to running 2-3/8" OD N-80 Tubing with Vann Tool Company. Tubing conveyed perforating gun to test Morris Zone from 11,079 feet to 11,092 feet.

JUN 23 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE June 18, 1976

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount and method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking for approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963 O-685229

847-485

RECEIVED

1978

RECEIVED

RECEIVED

1978