DISTRIBUTION SANTA FE	•	RECEIVE J	Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65
U.S.G.S. LAND OFFICE OPERATOR		JUL 9 1976 D. C. C. ARTERIA, OFFICE	Su, Indicate Type of Lease State X Fee 5, State Oll & Gas Lease No.
USE "APPLICATE	Y NOTICES AND REPORTS ON	WELLS	E-5313
2. Name of Operator	отнея.		7. Unit Agreement Reme Empire Abo Pressure Maintenance Project 8. Form of Lease Rume
Atlantic Richfield Compa 3. Address of Operator P. O. Box 1710, Hobbs, 1			Empire Abo Unit "L" 9. Well No. 132
4. Location of Well	43 FEET FROM THE West	LINE AND 275 FE	10. Field and Pool, or Wildcat Empire Abo
THE South LINE, SECTION	N 2 TOWNSHIP 18S	RANGE 27E	_HMPM.
	15. Elevation (Show whether 3536.3	3' GR	12. County Eddy
NOTICE OF IN	appropriate Box To Indicate N TENTION TO:		or Other Data QUENT REPORT OF:
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	PLUG AND ABANDON CHANGE PLANS	REMEDIAL WORK COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JQB OTHER LOG, Perforat	ALTERING CASING PLUG AND ABANDONMENT X Prod Csg e, Treat & Complete X
17. Describe Proposed or Completed Ope	erations (Clearly state all pertinent deta	ils, and give pertinent dates, in	cluding estimated date of starting any proposed
Finished drlg 7-7/8" hole 231' of 5½" OD 15.5# 8R K-55 LT&C csg on top. 5½ pmpd 10 bbls SAM-4 spacer salt, 5# Gilsonite & ¼# ff 4189' & circ out 100 sx cr HLV cmt w/8# salt/sk & 1006/26/76. Circ 85 sx out. stage collar @ 4189' & low 1000# 30 mins, OK. Ran car Ran compl assy as follows 1.81" profile, 1 jt 2-3/8 set pkr @ 5869', btm of the sequestering agent follows 5971-5983' 2½ hrs, rec 48	-55 LT&C csg on btm w/FS "OD csg set @ 6187' RKB. & 25 BFW followed by 475 locele/sk. Bumped plug v mt. Cmtd 2nd stage thru O sx C1 C w/8# salt/sk. Had full returns to sur wered bit to btm @ 6075', ased hole GR-Neutron log. : 1 jt 2-3/8" OD EUE tbg "OD EUE tbg, 1 - 1.81"BI bg @ 5904'. Trtd perfs 5 ed by 12 BLC. MP 2350#, BLW, tr oil. Well kicke	& FC. FC @ 6150'. DV tool @ 4189'. Sx Cl C 50/50 Pozm v/2000#, full return DV tool @ 4189' by Bumped plug & closerf. Inst wellhead o drld cmt 6075-6154. Perf'd Abo fm 5971 for TP, l Lok-set pFC "F" nipple & 1855971-5983' w/3000 ga Min 2150#, ISIP 200 ed off flwg. On 24	pmpg 50 BFW followed by 800 sx d collar w/2000# @ 3:30 AM n 6/26/76. Drld out cmt & ' PBD. Press tstd csg to -5983', 2 JSPF total 25 holes. kr, Model "FL" on-off tool, jts 2-3/8" OD EUE 8rd J-55 tbg
18. I hereby certify that the information w	hove is true and complete to the hest of	f my knowledge and helter	
зынсь Дом	•	ist. Drlg. Supv.	DATE 7/7/76
-PROVID BY W. a. Dres	set TITLE S	SUPERVISOR, DISTRICT	
CONDITIONS OF APPROVAL, IF ANYI	•		•