

**UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

N. M. O. C. C. COPY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 058126

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

**Ballard Grayburg
San Andres Unit**

8. FARM OR LEASE NAME

Tract No. 6

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

**Loco Hills Queen
Grayburg San Andres**

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

6 - 18S - 29E

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒

X - Water Injection

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Box 67, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

**1980' FSL & 2080' FEL, Sec. 6, T 18S, R29E
Eddy County, New Mexico**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3616.2 GL

12. COUNTY OR PARISH

13. STATE

Eddy New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

REPAIRING WELL

☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Commence Drlg. Operations X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12 1/4" hole 8-20-76, drilled to 380' KB, set 364' of 8 5/8" casing with guide shoe at 373' KB. Cemented with 150 sacks of Class H cement w/2% CaCL. Cement did not circulate, put 8 yards gravel down backside of casing. Installed and tested Series 900 double ram hydraulic blowout preventor. Drilled 7 7/8" hole to T. D. - 2750', set 27 1/4" of 4 1/2" casing at 2750' KB and cemented with 250 sacks Class H with .3 of 1% CFR-2, 5# salt/sack and 10# sand/sack.

Will complete at a later date and file appropriate forms.

RECEIVED

SEP 10 1976

**D. C. C.
ARTESIA, OFFICE**

RECEIVED

SEP 07 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

**Original Signed by
Jerry E. Buckles**

TITLE

Area Supervisor

DATE

August 26, 1976

(This space for Federal or State office use)

APPROVED BY

Joe D. Lam

TITLE

ACTING DISTRICT ENGINEER

DATE

SEP 8 1976

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.