

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ X - Water Injection Well		5. LEASE DESIGNATION AND SERIAL NO. LC 058127
2. NAME OF OPERATOR Anadarko Production Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 67		7. UNIT AGREEMENT NAME Ballard Grayburg San Andres Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1980' FEL Sec. 17, T 18S, R 29E Eddy County, New Mexico		8. FARM OR LEASE NAME Tract No. 7
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3499.6 GR	9. WELL NO. 3
		10. FIELD AND POOL, OR WILDCAT Loco Hills Queen Grayburg San Andres
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 17 - 18S - 29E
		12. COUNTY OR PARISH Eddy
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Commence Drlg. Operations	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded 12 1/2" hole 8-26-76, drilled to 387' KB, set 375' of 8 5/8" casing @ 386' KB. Cemented with 150 sacks Class H with 2% CaCL. WOC.

Installed and tested Series 900 double ram hydraulic blowout preventor.

Drilled 7 7/8" hole to T. D. - 2770', set 2764' of 4 1/2" casing @ 2770' KB and cemented with 250 sacks Class H with .3 of 1% CFR-2, 5# Salt/sack & 10# sand/sack.

Will complete at a later date and file appropriate forms.

RECEIVED

SEP 10 1976

O. C. C.
ARTESIA, OFFICE

RECEIVED

SEP 07 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed by Jerry E. Buckles TITLE Area Supervisor DATE September 3, 1976

(This space for Federal or State office use)

APPROVED BY Joe D. Lara TITLE ACTING DISTRICT ENGINEER

DATE SEP 8 1976

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.