Det. 1973       Budget Bureau No. 42-R1424         DEPARTMENT OF THE INTERORE GEOLOGICAL SURVEY       LC. 050906         SUNDRY NOTICES AND REPORTS ON WELLS       6. IF INDIAN, ALLOTTE OR TRIBE NAME         SUNDRY NOTICES AND REPORTS ON WELLS       0. UNIT AGREEMENT NAME         Co. not use this form for proposals to drill or to transport the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the bis/held different feervire, Use Form 3-31-C for such proposals to drill or to transport to the transport to thetransport to the transport to the transport to the transport to th		NM OIL CONS.	COMMIS	Form Amound	Yð
DEPARTMENT OF THE INTERVED GEOLOGICAL SURVEY       L. C. COCO906         SUNDRY NOTICES AND REPORTS ON WELLS Denote use the form the production of the software or page badful denotes and DEST of the form the production of the software o		CWGL III		Form Approved. Budget Bureau No. 4	42-R1424
DEPARTMENT OF THE INTERVED GEOLOGICAL SURVEY       L. C. COCO906         SUNDRY NOTICES AND REPORTS ON WELLS Denote use the form the production of the software or page badful denotes and DEST of the form the production of the software o		In cesia, NM	3210. LEASE		· · · · · · · · · · · · ·
SUNDRY NOTICES AND THE PORTS ON WELLS The net use the form the persentation of any general pack baland diverses BOS #	DEPARTMENT OF THE INTE	EVED	LC		·
Ballard Grayburg San Andres Unit         1. off       Ballard Grayburg San Andres Unit         1. off       Ballard Grayburg San Andres Unit         2. NAME OF PERIOR       Ballard Grayburg San Andres Unit         3. ADDRESS OF OPERATOR       9. WELL NO. 5         9. OLDENT OF WELL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR LEASE NAME         4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR ULASE NAME         4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR ULASE NAME         10. FIELD OR WILL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR ULASE NAME         11. SEC. T. R. M., OR BLK. AND SURVEY OR       AREA         12. COUNTY OR WELL (REPORT LOCATION CLEARLY. See space 17       B. FIELD OR WILDCAT NAME         13. DIFFECTION (SHOW DF KLEARLY NEW MAXICO       10. FIELD OR WILDCAT NAME         14. AT OP PROD. INTERVAL:       Same State 10         15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       B. FIELON (SHOW DF, KDB, AND WD)         15. TOTAL DEPTH:       Same State 10         15. MELT AND ALTER DATA       STATE         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       B. FIELD OR WELL MONONE         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       B. FIELD OR WELL MONONE         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent deta	GEOLOGICAL SURVEY		6. IF INDIAN,	ALLOTTEE OR TRIBE N	AME
Ballard Grayburg San Andres Unit         1. off       Ballard Grayburg San Andres Unit         1. off       Ballard Grayburg San Andres Unit         2. NAME OF PERIOR       Ballard Grayburg San Andres Unit         3. ADDRESS OF OPERATOR       9. WELL NO. 5         9. OLDENT OF WELL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR LEASE NAME         4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR ULASE NAME         4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR ULASE NAME         10. FIELD OR WILL (REPORT LOCATION CLEARLY. See space 17       B. FARM OR ULASE NAME         11. SEC. T. R. M., OR BLK. AND SURVEY OR       AREA         12. COUNTY OR WELL (REPORT LOCATION CLEARLY. See space 17       B. FIELD OR WILDCAT NAME         13. DIFFECTION (SHOW DF KLEARLY NEW MAXICO       10. FIELD OR WILDCAT NAME         14. AT OP PROD. INTERVAL:       Same State 10         15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       B. FIELON (SHOW DF, KDB, AND WD)         15. TOTAL DEPTH:       Same State 10         15. MELT AND ALTER DATA       STATE         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       B. FIELD OR WELL MONONE         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       B. FIELD OR WELL MONONE         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent deta	AND AND AND AND AND AND	1 24 M 84			<u>-</u>
Present Use Form 9-3112 for use properties of the properties					s Init
	reservoir. Use Form 9-331-C for such proposals				<u></u>
2. NAME OF OPERATOR       13         Anadarko Production Company       10. FIELD OR WILDCAT NAME Loca Hills=Queen-Grayburg-San And 11. SEC. T. R. M., OR BLK. AND SURVEY OR ALCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 Networks of PROP. INTERVAL: Same AT TOP AND FOR MITERVAL: Same AT TOP AND FORD. INTERVAL: Same AT TOP AND FROM LOCATION CLEARLY. See space 17 Networks of PARISH 13. STATE Eddy       12. COUNTY OF PARISH 13. STATE Eddy       12. COUNTY OF PARISH 13. STATE Eddy       14. API NO.         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA       IS. ELEVATIONS (SHOW DF, KDB, AND WD) 3491.7' GL         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details, and not state of stating any proposed work. If well is directionally drinled, give subsurface locations and message and true vertical depths for all markers and anose pertinent details, and give pertinent detas. Including estimated date of stating any proposed work. If well is directionally drinled, give subsurface locations and message boles @ 2180 <sup>4</sup> and set CIBP @ 2250 <sup>4</sup> REPARENT Solution of 2004. REPARENT Solution of 2004 and established circulation rate of 3 BPM @ 5006. Pumped 1 as red dyze and followed with 300 bbl brin water; did not see dys ereturn. Cemented with 1500 sx Halliburton Lite cement with 18 <sup>4</sup> Salt/ax and the flocele/ax. Tailed in with 100 ax Class C cement with 21 CaCl.         Set @	1. oil 🗂 gas 📊	Inj. Well		ct No. 5	
ADDRESS OF OPERATOR      P. O. Drawer 130, Artesia, New Mexico 88210      A. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17     below.)     ALL CARTON OF WELL (REPORT LOCATION CLEARLY. See space 17     below.)     AT SURFACE: 1310' FSL & 20' FEL Sec. 8, T185,     AT TOP PROD. INTERVAL: Same     REPORT, OR OPRICE BOX     Same     Same     CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.     REPORT, OR OPRICE DATA     SUBSEQUENT REPORT OF RECEIVED BY     REPORT, OR CLOZE     SUBSEQUENT REPORT OF RECEIVED BY     MAY 91984     Not Marked addition of multiple completion or zone     OLC O. D. Change of form 9-330.)     ARTESIA, OFFICE     ARTE CASING     MULTIPLE COMPLETE     MAY 91984     Not Marked addition of the subsurface locations and     messured and true vertical depths for all markers and some pertinent details, and give pertinent dates,     including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and     messured and true vertical depths for all markers and some pertinent to this work.'      Kigged up pulling unit; tripped out of hole with packers.     Ran Cement Bond Log and found cement top 02 (194').     Set formed ad in the vertical depths for all markers and set CIBP (9 2250'     Set cement retainer (2 140' and established circulation rate of 3 BPM (9 5004.     Pumped 1 screed ye and followed with 300 bbb brine water; did not see dye return.     Cemented with 1500 ax Class C cement with 12 % CaCl. Cement to did prot circulate. TOH     Ran Temperature Survey after 8 hours and found cement top (8 490'.     Start 11 do ut top of CIBP and pushed down hole to 3090'; TOH.     Continued on page 2.     Subsurface Safety Valve: Manu. and Type     MAY 81984     'See instructions on Revers Side	2. NAME OF OPERATOR /	<b>v</b>		13	
P. O. Drawer 130, Artesia, New Mexico 88210       11. SEC. T. R. M. OR BLK. AND SURVEY OR 'AREA' ALCA' AND ALCONTO OF WELL (REPORT LOCATION CLEARLY. See space 17' AREA' & - 18S - 29E         A. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17' AREA' & - 18S - 29E       12. COUNTY OR PARISH '13. STATE         AT TO'AL DEPT'H: Same       8.29E       12. COUNTY OR PARISH '13. STATE         AT TO'AL DEPT'H: Same       REYE       14. API NO.         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       15. ELEVATIONS (SHOW DF, KDB, AND WD)         REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT O'RECEIVED BY         PARCTURE TREAT       Image: Complete By         SHORT OR ACIDZE       Image: Complete By         PULL OR ALTER CASING       Image: Complete By         MULTIPLE COMPLETE       Image: Complete By         PULL OR ALTER CASING       Image: Complete By         MULTIPLE COMPLETE       Image: Complete By         ABANDON*       Image: Complete By         ABANDON*       Image: Complete By         ABANDON*       Image: Complete By         Pull OR ALTER CASING       Image: Complete By         Pull By       Set Complete By					
4. ICCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below).       AREA 8 - 185 - 29E         AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same       B. 29E         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA       II. COUNTY OR PARISH       13. STATE Eddy         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA       SUBSEQUENT REPORT OF RECEIVED BY WAY 9.1984 (NOTE Report results of multiple completion or zone O. C. D. change of form 9-330.3         7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for and markers and comes pertinent to this work.?         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for a comes pertinent to this work.?         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for a comes pertinent to this work.?         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for andows and fore specive startis date of a BPH @ 50004. </td <td></td> <td>Marica 88210</td> <td></td> <td></td> <td></td>		Marica 88210			
below.)       AT SURFACE: 1310' FSL & 20' FEL Sec. 8, T185, AT TOP PROD. INTERVAL: Same       829E         16. CHECK APPROPRIATE Same       12. COUNTY OR PARISH 13. STATE Eddy       New Mexico         16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA       14. API NO.       14. API NO.         16. CHECK APPROPRIATE TO TO THER DATA       SUBSEQUENT REPORT OF PROVIDE TO THER DATA       15. ELEVATIONS (SHOW DF, KDB, AND WD) 3491.7' GL         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of stating any proposed work. If well is directionally direct operating of the state of the state of the state all pertinent details, and give pertinent dates, including estimated date of stating any proposed work. If well is directionally direct operations and an measured and true vertical depths for all markers and zones pertinent to this work.)*         Rigged up pulling unit; tripped out of hole with packers. Ran Cement Bond Log and found cement top @ 2194'.         Rement Bond Log and found cement top @ 2194'.         Perforated 2 squeeze holes @ 2188' and set CIBP @ 2250'         Set cement retainer @ 2140' and established circulation rate of 3 BPH @ 5009.         Pumped 1 sx red dye and followed with 300 bbl brine water; did not see dye return. Cemented with 1500 sx Class C cement with 27. CaCl.         Ran temperature Survey after 8 hours and found cement top @ 400'. Braidenhead squeezed with 300 sx Class C cement with 27. CaCl.         Subsurface Safety Valve: Manu. and Type		······································		, M., UR BLK. AND SU	RVEY OR
AT TOP PROD. INTERVAL:       Same       R29E       Eddy       New Mexico         Id. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       Id. API NO.       Id. API NO.       Id. API NO.         Id. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       Id. API NO.       Id. API NO.       Id. API NO.         REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF RECEIVED BY       Id. API NO.       Id. API NO.         FRACTURE TRAT       Id. MAY 9 1964       Id. API NO.       Id. API NO.         SHOOT OR ACIDIZE       Id. MAY 9 1964       Id. API NO.       Id. API NO.         PULL OR ALTER CASING       Id. API NO.       Id. API NO.       Id. API NO.         IV.LUPRE COMPLETE       Id. API NO.       Id. API NO.       Id. API NO.         IV.LUPRE COMPLETE       Id. API NO.       Id. API NO.       Id. API NO.         IV.LUPRE COMPLETE       Id. API NO.       Id. API NO.       Id. API NO.         IV.LUPRE COMPLETE       Id. API NO.       Id. API NO.       Id. API NO.         IV.LUPRE COMPLETE       Id. API NO.       Id. API NO.       Id. API NO.         IV.LUPRE COMPLETE       Id. API NO.       Id. API NO.       Id. API NO.         IV.LUPRE APROVALE APROVE	below.)	·	8 -	185 - 29E	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA       15. ELEVATIONS (SHOW DF, KDB, AND WD) 3491.7' GL         REQUEST FOR APPROVAL TO: FEST WATER SHUT-OFF FACTURE TREAT SHOOT OR ACIDIZE REPAR WELL PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* (other)       SUBSEQUENT REPORT OF RECEIVED BY MAY 9.1964 (NOTE Report results of multiple completion or zone O. C. D. ARTESIA, OFFICE         17. DESCRIEE PROPOSED OR COMPLETED OPERATIONS (Clearly state all partinent details, and give partinent dates, including estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*         17. DESCRIEE PROPOSED OR COMPLETED OPERATIONS (Clearly state all partinent details, and give partinent dates, including estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* <b>17. DESCRIEE</b> PROPOSED OR COMPLETED OPERATIONS (Clearly state all partinent details, and give partinent dates, including estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* <b>18.</b> Igged up pulling unit; tripped out of hole with packers. <b>19.</b> Cement With 100 as K all set Class C cement with 184 Salt/Ax and 14 Flocele/sx. <b>19.</b> Cancer with 100 as Class C cement with 2% CaCl. Cement did not circulate. TOH Ran Temperature Survey after 8 hours and found cement top 0 490'. <b>11.</b> Id out top of CLBP and pushed down hole to 3090'; TOH. Continued on pag	AT TOP PROD. INTERVAL: Same	· · · · ·			cico
REPORT, OR OTHER DATA       15. ELEVATIONS (SHOW DF, KDB, AND WD) 3491,7' GL         REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT       SUBSEQUENT REPORT OF FRECEIVED BY MAY 9 1984 WAY 9 1984 WAY 9 1984 WAY 9 1984 MAY 9 1984         PULL OR ACIDIZE REPARE WELL CHANGE ZONES ABANDON*       MAY 9 1984 WAY 9 1984 MAY 9 1984 MAY 9 1984         10. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all partinent details, and give partinent dates, including estimated date of starting any proposed work, if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.''         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all partinent details, and give partinent dates, including estimated date of starting any proposed work, if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.''         18. December BOND LOG and found cement top (2 2194'.         Perforated 2 squeese holes (2 188' and set CIBP (2 2250' Set cement retainer (2 140' and established circulation rate of 3 BPM (9 5004.         Pumped 1 sx red dye and followed with 300 bbl brine water; did not see dye return. Cemented with 1500 sx Class C cement with 2% CaCl.         WIH with bit and drilled out cement retainer and cement; tested squeese holes to 8006'; held good.         Drilled out top of CIBP and pushed down hole to 3090'; TOH. Continued on page 2.         Subsurface Safety Valve: Manu. and Type         MAY 8 1984		an a			
Is the first of the form		ATURE OF NOTICE	· · · · · · · · · · · · · · · · · · ·		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF RECEIVED BY FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING PULL OR ALTER CASING PULL OR ALTER CASING PULL OR ALTER CASING PULL OR ALTER CASING WILTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perliment to this work.)* Rigged up pulling unit; tripped out of hole with packers. Ran Cement Bond Log and found cement top @ 2194'. Perforated 2 squeeze holes @ 2188' and set CIBP @ 2250' Set cement retainer @ 2140' and established circulation rate of 3 BPN @ 500\$. Pumped 1 sx red dye and followed with 300 bbl brine water; did not see dye return. Cemented with 1500 sx Halliburton Lite cement with 185' Salt/sx and 4% Flocele/sx. Tailed in with 100 sx Class C cement with 2% CaCl. Cement did not circulate. TOH Ran Temperature Survey after 8 hours and found cement top @ 400'. Braidenhead squeesed with 300 asx Class C cement with 12% CaCl. WIH with bit and drilled out cement retainer and cement top & 400'. Braidenhead squeesed with 300 asx Class C cement with 2% CaCl. WIH with bit and drilled out cement retainer and cement; tested squeese holes to 8006'; held good. Drilled out op of CIBP and pushed down hole to 3090'; TOH. Continued on page 2. Subsurface Safety Valve: Manu. and Type MAY 8 1984 "See Instructions on Reverse Side					ND WD)
FRACTURE THEAT	REQUEST FOR APPROVAL TO: SUBSEQUI	INT REPORT OF			
SHOOT OR ACIDIZE       Image: Comparison of the second state state state state state state of the second state state state state state state state state state of the second state of the second state state state state state of the second state of the second state state state state of the second state of the second state state state of the second state state state state state state state state state state. Toke second state st			CLIVED BY	1	
REFAIR WELL       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of multiple completion or zone         MULTIPLE COMPLETE       Indiff Property regins of Tom 9-330.)         Multiple completion of the sector       Arter Cashed         Indicating any proposed work. If well is directionally drilled, give subsurface locations and property regins of an and sectors.         Random of the sector of the sector.       Random of the sector of the sector.         Cement d z squeeze holes of all out cement with 184 Salt/sx and 144 Plocele/sx.       Cement did not circulate. TOH         Ran temperature Survey after 8 hours and found		MA	Y 9 100%	1	
MULTIPLE COMPLETE			(NOTE: Report r	esults of multiple completi	on or zone
ABADON*			$\mathbf{D}_{\mathbf{C}}$ $\mathbf{D}_{\mathbf{C}}$	51. Form 9–330.)	
(other)       XX - Cement Water Flow         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*         18       Item that the starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*         19       Item that the starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*         10       Item that the starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*         11       Item that the starting and found cement top @ 2194'.         12       Perforated 2 squeese holes @ 2188' and set CIBP @ 2250'         13       Set cement retainer @ 2140' and established circulation rate of 3 BPM @ 500#.         11       Cement did not see dye return.         12       Cement with 1500 as Halliburton Lite cement with 18# Salt/as and ¼# Plocele/as.         13       Interface & squeesed with 300 as Class C cement with 2% CaCl.         Will with bit and drilled out cement retainer and cement; tested squeese holes to 800#; held good.       Soutil to of CIBP and pushed down hole to 3090'; TOH. <th></th> <th>ART</th> <th>ESIA, OFFICE</th> <th>]</th> <th></th>		ART	ESIA, OFFICE	]	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*         Rigged up pulling unit; tripped out of hole with packers.         Ran Cement Bond Log and found cement top @ 2194'.         Perforated 2 squeeze holes @ 2188' and set CIBP @ 2250'         Set cement retainer @ 2140' and established circulation rate of 3 BPM @ 500#.         Pumped 1 sx red dye and followed with 300 bbl brine water; did not see dye return.         Cemented with 1500 sx Halliburton Lite cement with 18# Salt/sx and ½# Flocele/sx.         Tailed in with 100 ax Class C cement with 2 % CaCl. Cement did not circulate. TOH         Ran Temperature Survey after 8 hours and found cement top @ 490'.         Braidenhead squeezed with 300 ax Class C cement with 2% CaCl.         Will with bit and drilled out cement retainer and cement; tested squeeze holes to 800#; held good.         Drilled out top of CIBP and pushed down hole to 3090'; TOH.         Continued on page 2.         Subsurface Safety Valve: Manu. and Type         Iter Field Foreman       Date         MAY 81984         Value Mark 100 For APPROVAL Mark         Mark 100 RecORD         Mark 100 RecORD         Note: Mark 1984		C - Cement Wat	er Flow		
Ran Cement Bond Log and found cement top @ 2194'. Perforated 2 squeeze holes @ 2188' and set CIBP @ 2250' Set cement retainer @ 2140' and established circulation rate of 3 BPM @ 500#. Pumped 1 sx red dye and followed with 300 bbl brine water; did not see dye return. Cemented with 1500 sx Halliburton Lite cement with 18# Salt/sx and ½# Plocele/sx. Tailed in with 100 ax Class C cement with 2% CaCl. Cement did not circulate. TOH Ran Temperature Survey after 8 hours and found cement top @ 490'. Braidenhead squeezed with 300 sx Class C cement with 2% CaCl. WIH with bit and drilled out cement retainer and cement; tested squeeze holes to 800#; held good. Drilled out top of CIBP and pushed down hole to 3090'; TOH. Continued on page 2. Subsurface Safety Valve: Manu. and Type	including estimated date of starting any prop measured and true vertical depths for all mark	osed work. If well is ers and zones pertin	directionally drilled ent to this work.)*	tails, and give pertine , give subsurface locat	nt dates, tions and
Set cement retainer @ 2140' and established circulation rate of 3 BPM @ 500#. Pumped 1 sx red dye and followed with 300 bbl brine water; did not see dye return. Cemented with 1500 sx Halliburton Lite cement with 18# Salt/sx and ½# Flocele/sx. Tailed in with 100 sx Class C cement with 2 % CaCl. Cement did not circulate. TOH Ran Temperature Survey after 8 hours and found cement top @ 490'. Braidenhead squeesed with 300 ax Class C cement with 2% CaCl. WIH with bit and drilled out cement retainer and cement; tested squeese holes to 800#; held good. Drilled out top of CIBP and pushed down hole to 3090'; TOH. Continued on page 2. Subsurface Safety Valve: Manu. and Type	Ran Cement Bond Log and found ceme	ent top @ 2194	· •		
Pumped 1 sx red dye and followed with 300 bbl brine water; did not see dye return. Cemented with 1500 sx Halliburton Lite cement with 18# Salt/sx and ½# Flocele/sx. Tailed in with 100 sx Class C cement with 2 % CaCl. Cement did not circulate. TOH Ran Temperature Survey after 8 hours and found cement top @ 490'. Braidenhead squeesed with 300 sx Class C cement with 2% CaCl. WIH with bit and drilled out cement retainer and cement; tested squeese holes to 800#; held good. Drilled out top of CIBP and pushed down hole to 3090'; TOH. Continued on page 2. Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct SIGNED Mike Burnel TITLE Field Foreman December 30, 1983 ACCEPTED FOR RECORD APPROVED BY	Perforated 2 squeeze holes @ 2188	and set CIBP	@ 2250'	OF 3 BON @ 500	ነፈት
Cemented with 1500 sx Halliburton Lite cement with 18# Salt/sx and ½ Flocele/sx. Tailed in with 100 sx Class C cement with 2 % CaCl. Cement did not circulate. TOH Ran Temperature Survey after 8 hours and found cement top @ 490'. Braidenhead squeesed with 300 sx Class C cement with 2% CaCl. WIH with bit and drilled out cement retainer and cement; tested squeese holes to 800#; held good. Drilled out top of CIBP and pushed down hole to 3090'; TOH. Continued on page 2. Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct SIGNED Min. Brunch TITLE Field Foreman Date Conditions of APPROVAL WAY 8 1984 *See Instructions on Reverse Side					
Tailed in with 100 sx Class C cement with 2% CaCl. Cement did not circulate. TOH         Ran Temperature Survey after 8 hours and found cement top @ 490'.         Braidenhead squeezed with 300 sx Class C cement with 2% CaCl.         WIH with bit and drilled out cement retainer and cement; tested squeeze holes to 800%; held good.         Drilled out top of CIBP and pushed down hole to 3090'; TOH.         Continued on page 2.         Subsurface Safety Valve: Manu. and Type         Stance         Signed         MAY         ACCEPTED FOR RECORD         APPROVED BY         MAY         Subsurface Side					
Braidenhead squeezed with 300 ax Class C cement with 2% CaCl. WIH with bit and drilled out cement retainer and cement; tested squeeze holes to 800#; held good. Drilled out top of CIBP and pushed down hole to 3090'; TOH. Continued on page 2. Subsurface Safety Valve: Manu. and Type	Tailed in with 100 sx Class C ceme	ent with 2 % C	aC1. Cement	did not circula	te. TOH
WIH with bit and drilled out cement retainer and cement; tested squeese holes to 800#; held good. Drilled out top of CIBP and pushed down hole to 3090'; TOH. Continued on page 2. Subsurface Safety Valve: Manu. and Type					
800#; held good.         Drilled out top of CIBP and pushed down hole to 3090'; TOH.         Continued on page 2.         Subsurface Safety Valve: Manu. and Type	WIH with bit and drilled out cemer	nt retainer an	d cement: tes	ted squeese hol	les to
Continued on page 2.         Subsurface Safety Valve: Manu. and Type	800#; held good.		•	•	
Subsurface Safety Valve: Manu. and Type       Set @Ft.         18. I hereby certify that the foregoing is true and correct	Drilled out top of CIBP and pushed	l down hole to		•	
18. I hereby certify that the foregoing is true and correct         SIGNED Min. Brunnell       Field Foreman       December 30, 1983         (This space for Federal or State office use)         ACCEPTED FOR RECORD         ATTLE       DATE         MAY 81984         *See Instructions on Reverse Side					
SIGNED       May       81984         Field Foreman       Date         December 30, 1983         MAY       8 1984         *See Instructions on Reverse Side	Subsurface Safety Valve: Manu. and Type			Set @	Ft.
This space for Federal or State office use)  ACCEPTED FOR RECORD  APPROVED BY  CONDITIONS OF APPROVAL, MAY  8 1984  *See Instructions on Reverse Side					_
CONDITIONS OF APPROVAL, MAY 8 1984 MAY 8 1984 *See Instructions on Reverse Side	SIGNED Mike Brannell TITL	E Field Foren	DATE DE	cember 30, 1983	3
CONDITIONS OF APPROVAL, MAY 8 1984 MAY 8 1984 *See Instructions on Reverse Side	(This spa	ce for Federal or State	office use)		
MAY 8 1984 *See Instructions on Reverse Side	APPROVED BY	LE	DATE		<u> </u>
ROSWELL, NEWLANEXICO	*See	Instructions on Revers	e Side		
	ROSWELL NEWL MEXICO				

orm 9–331 Dec. 1973	Form Approved. Budget Bureau No. 42-R1424			
UNITED STATES	5. LEASE			
DEPARTMENT OF THE INTERIOR	LC 050906			
GEOLOGICAL REPERVEN	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME			
Do not use this form for proposals to negligible to deepen or plug back to a different eservoir. Use Form 9–331–C for such and the servoir of	Ballard Grayburg San Andres Unit			
	8. FARM OR LEASE NAME			
1. oil gas other X - Dual Ini, Well	Tract No. 5			
······································	9. WELL NO.			
2. NAME OF OPERATOR				
Anadarko Production Company	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR	Loco Hills-Queen-Grayburg-San And 11. SEC., T., R., M., OR BLK. AND SURVEY OR			
P. O. Drawer 130, Artesia, New Mexico 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA			
4. LOCATION OF WELL (REPORT EDGATION CLEARLY. See space 17 below.)	8 - 185 - 29E			
AT SURFACE: 1310' FSL & 20' FEL Sec. 8,T18S, AT TOP PROD. INTERVAL: Same R29E	12. COUNTY OR PARISH 13. STATE Eddy New Mexico			
AT TOTAL DEPTH: Same	14. API NO.			
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,				
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3491.7° GL			
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:				
EST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)			
IULTIPLE COMPLETE     I       HANGE ZONES     I       BANDON*     I       bother)     XX - Cement Wate	r Flow			

## Page 2

10. WIH with 4½" packer on 2-3/8" Salta (internally plastic lined) tubing. Circulated chemical and fresh water down casing annulus. Tested casing to 800# in accordance with NMOCC Rules & Regulations. 11. Set packer @ 2418' and returned well to injection.

Subsurface Safety Valve: Manu. and Type			· · · · · · · · · · · · · · · · · · ·	Set @			Ft.	
18. I hereby certify that the foregoing is tr SIGNED Mike Brannell			Foreman	DATE	December	30,	1983	
ACCEPTED FOR REC	ด์สด		or State office us				-	
APPROVED BY CONDITIONS OF APPROVAL, ALC AND STREAM		·						
	*See In:	structions a	n Reverse Side					

ROGWELL, NEW MEXICO