

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE **RECEIVED**

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy _____	T. Canyon _____	8536	T. Ojo Alamo _____	T. Penn. "B" _____	OCT 1 1976
T. Salt _____	T. Strawn _____	9149	T. Kirtland-Fruitland _____	T. Penn. "C" _____	
B. Salt _____	T. Atoka _____	9796	T. Pictured Cliffs _____	T. Penn. "D" _____	D. C. C.
T. Yates _____	T. Miss _____		T. Cliff House _____	T. Leadville _____	ARTESIA, OFFICE
T. 7 Rivers _____	T. Devonian _____		T. Menefee _____	T. Madison _____	
T. Queen _____	T. Silurian _____		T. Point Lookout _____	T. Elbert _____	
T. Grayburg _____	T. Montoya _____		T. Mancos _____	T. McCracken _____	
T. San Andres _____	T. Simpson _____		T. Gallup _____	T. Ignacio Qtzte _____	
T. Glorieta _____	T. McKee _____		Base Greenhorn _____	T. Granite _____	
T. Paddock _____	T. Ellenburger _____		T. Dakota _____	T. _____	
T. Blinberry _____	T. Gr. Wash _____		T. Morrison _____	T. _____	
T. Tubb _____	T. Granite _____		T. Todilto _____	T. _____	
T. Drinkard _____	T. Delaware Sand _____		T. Entrada _____	T. _____	
T. Abo _____	T. Bone Springs _____		T. Wingate _____	T. _____	
T. Wolfcamp _____	T. Mwr. Clastics _____	10236	T. Chinle _____	T. _____	
T. Penn. _____	T. Chester _____	10688'	T. Permian _____	T. _____	
T. Cisco (Bough C) _____	T. _____		T. Penn. "A" _____	T. _____	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	170	170	Surface & gravel				
170	498	328	Surface & sand				
498	688	190	Sand & dolomite				
688	1050	362	Sand				
1050	1765	715	Lime & sand				
1765	1999	234	Lime				
1999	2145	146	Lime & Anhydrite				
2145	2400	255	Lime				
2400	2732	332	Dolomite				
2732	8216	5484	Lime				
8216	9040	824	Lime & shale				
9040	9106	66	Lime, shale & dolomite				
9106	9276	170	Lime & shale				
9276	9473	197	Shale				
9473	9546	73	Lime & shale				
9546	9600	54	Lime				
9600	9738	138	Lime & shale				
9738	9902	164	Shale				
9902	10112	210	Lime & shale				
10112	10235	123	Shale & sand				
10235	10314	79	Shale & lime				
10314	10730	416	Shale				