

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 V
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION  
OCT 28 1976

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

**O. C. C.**  
**ARTESIA, OFFICE**

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
Rio Pecos "GB" Com	
9. Well No.	
1 1	
10. Field and Pool, or Wildcat	
Und Red Lake Penn.	
12. County	
Eddy	

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Yates Petroleum Corporation
3. Address of Operator
207 South 4th Street - Artesia, NM 88210
4. Location of Well
UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 29 TOWNSHIP 18S RANGE 27E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3305' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Set Production casing & Perf

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 9768; PBTD 9623'. - Ran 215 joints of new 5½" casing as follows w/9 centralizers.

1-Howco Guide Shoe	2.08'
1-Jt 5½" 17# N-80 LT&C csg.	41.08'
1-Howco 5½" Diff Fill-Float Collar	1.75'
31-jts 5½" 17# N-80, LT&C csg.	1379.22'
D. V. Tool #54	2.73'
167-jts 5½" 17# K-55 LT&C csg.	7453.72'
16-jts 5½" 17# N-80, LT&C csg.	721.99'
<b>Total</b>	<b>9602.57'</b>
<b>Below KB</b>	<b>20.00'</b>
<b>Set at</b>	<b>9622.57'</b>

(Howco D. V. Tool at 7220') (Preceded w/250 gallons of mud flush). Cemented by Howco in two stages as follows: 1st Stage: - 280 sx Lite 1/2% CFR-2 and 5# KCL, followed w/150 sacks Class H, 1/2% CFR-2 and 5# KCL. PD 3:45 PM 10-11-76. Dropped DV opening tool. Circulated 3½ hours between stages - (Cont'd on back)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Johnson TITLE Geol. Secty DATE 10-27-76

APPROVED BY W. A. Grasset TITLE SUPERVISOR, DISTRICT II DATE OCT 29 1976

CONDITIONS OF APPROVAL, IF ANY: