

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Yates Pet Corp.</i>		Lease <i>Reon Gk</i>		Well # <i>1</i>	
Location of Well	Unit/D <i>330 NW</i>	Section <i>27</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor	<i>Byrd & Co.</i>		Type of Equipment <i>Rotary</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
10 3/4 15"	10 3/4"	32		400	Cir.
9 1/2"	7"	20		1230	"
6 1/4"	4 1/2 x 5 1/2"	9.5 x 15.5		1800	"

Casing Data:

Surface 37 joints of 7 inch 23 # Grade Gilb New - Re-Used - All - N-80
API N-80 (Approved) (Rejected)

Inspected by Lelan Mennis date 9-14-76

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required 500/sy

Type of Shoe used Texas A&M Float collar used None Btm 2 jts welded Thread Lock

TD of hole 1214' KB Set 1201' GL Feet of 7" Inch 23 # Grade N-80

New-used csg. @ 1201' GL with 150 sacks neat cement around shoe Class 2 2% cc
+ 350 sax Class C Mix additives 6" Gilbonite 1/4" Flocele 2% cc

Plug down @ 8:25 (AM) (PM) Date 9-14-76

Cement circulated Yes No. of Sacks 20/sy

Cemented by Denton Witnessed by Lelan Mennis

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Water 50-237, 296-656, 777-784