

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr. Corp.</i>		Lease <i>Nix GP</i>		Well # <i>1</i>	
Location of Well	Unit <i>9903 2310e</i>	Section <i>22</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Byrd Drilling Co.</i>			Type of Equipment <i>Rotary</i>		

* *Witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>15"</i>	<i>10 3/4"</i>	<i>32</i>		<i>400</i>	<i>Circ.</i>
* <i>9 1/2"</i>	<i>7"</i>	<i>20</i>		<i>1200</i>	<i>"</i>
<i>6 1/4"</i>	<i>4 1/2 x 5 1/2"</i>	<i>10.5 + 15.5</i>		<i>1800</i>	<i>"</i>

Casing Data:

Surface *37* joints of *7"* inch *20* # Grade *used API J-55*
(Approved) (~~Rejected~~)

Inspected by *Lelan Messing* date *9-18-76*

Cementing Program

Size of hole *9 1/2"* Size of Casing *7"* Sacks cement required *500/sk*

Type of Shoe used *Texas A.M. Float* collar used *None* Btm *2* jts ~~welded~~ *Thread Lock*

TD of hole *1218 KB* Set *1205 6'* Feet of *7"* Inch *20* # Grade *J-55*

New-used csq. @ *1205'* with *150* sacks neat cement around shoe & *1-1/2* c 2% cc

