

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 V
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

OCT 22 1976

O. C. C.
ARTESIA. OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Flint "GU"	
9. Well No. 1 1	
10. Field and Pool, or Wildcat Und. Atoka San Andres	
12. County Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	4. Location of Well UNIT LETTER <u>J</u> <u>1650'</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>22</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3324' GR	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 9½" hole at 4:00 PM 10-14-76.

TD 1165' - Ran 36 joints of 7" 20# used casing (1165.20') set at 1165' KB. 1-Guide shoe and centralizers at 1133' and 649', baskets at 681' & 616'. Cemented by Denton w/350 sacks of mix w/2% CaCl followed w/150 sacks of Class C 2% CaCl. PD 10:30 PM 10-17-76. Cement circulated. After WOC 8 hours cement dropped 24'. Filled hole w/2 yards of Ready-Mis. WOC 18 hours NU and tested BOP's to 1000#. OK. Reduced hole to 6¼", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty. DATE 10-21-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE OCT 25 1976

CONDITIONS OF APPROVAL, IF ANY: