

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved,  
Budget Bureau No. 42 R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM 063472

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 17

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Wildcat Marrow  
11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Section 17, T18S - R30E

12. COUNTY OR PARISH 13. STATE

Eddy New Mexico

## SUNDRY NOTICES AND REPORTS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

DEC 15 1976

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR  
BELCO PETROLEUM CORPORATIONO. C. C.  
ARTESIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
10,000 Old Katy Road - Suite #100, Houston, Texas 77055  
At surface

1980' FSL, 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3486.0 Gr

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) spud; casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 11/26/76 Spudded 17½" hole. Drilled to 410'; ran & set 9 jnts 13-3/8" 48# csg @ 410'; cmt'd w/200 sx RFC cement + 250 sx Class "H" cement w/2% CaCl₂; did not circ.
- 11/27/76 Trip in hole w/1"; tagged cmt @ 175'; cmt'd w/200 sx Class "C" w/2% CaCl₂; cmt dropped 60' to 135'; cmt'd w/175 sx Class "C" w/2% CaCl₂; circ cmt.
- 12/4/76 Drilled to 3700'; ran & set 92 jnts 36 & 40# csg @ 3700'; cmt'd w/1280 sx Lite wt w/4% gel + 5# D-42 + 1/4# D-29 + 2% CaCl₂; tailed in with 200 sx Class "C" w/2% CaCl₂.
- 12/6/76 Tested 9-5/8" csg to 2000#; drlg cmt & float collar; tstd to 2000#; drlgd shoe & 3' of formation; tested to 400#; resumed drilling.

RECEIVED

DEC 13 1976

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Geologist

DATE 12/9/76

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

DEC 14 1976

CONDITIONS OF APPROVAL, IF ANY: