

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Mark Prod. Co.</u>		Lease <u>Swearingen A</u>		Well # <u>1</u>	
Location of Well	Unit <u>M</u> <u>9903</u> <u>6600</u>	Section <u>1</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>WEK.</u>	Type of Equipment <u>Rotary to start 11-15-76</u>				

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 7/8"</u>	<u>48</u>		<u>200</u>	<u>225 lin.</u>
* <u>11</u>	<u>8 7/8"</u>	<u>24</u>		<u>1150</u>	<u>450 "</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>17</u>		<u>1800</u>	<u>400 "</u>

Casing Data:

Int:
Surface 27 joints of 8 5/8 inch 24 # Grade API New J-55

(Approved) (Rejected)

Inspected by Selan G. Morris date 1-18-77

Cementing Program

Size of hole 11" Size of Casing 8 5/8 Sacks cement required 400/50

Type of Shoe used Guide Float collar used Insert + Btm 3 jts welded Thread-Back

TD of hole 1150' KB Set 1140' CL Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 1140' CL with 150/ sacks neat cement around shoe 1140' CL + 250/ sack Trinity Life water additives 5" @ 150' to 1/4" celloflake 2% cc

Plug down @ 3:00 PM (AM) (PM) Date 1-18-77

Cement circulated Yes No. of Sacks 10/50

Cemented by B. J. Witnessed by Selan G. Morris

Temp. Survey ran @ (AM) (PM) Date 1-18-77 top cement @ 11:15-76

Casing test @ (AM) (PM) Date 1-18-77

Method Used 11-15-76 Witnessed by 1-15-76

Checked for shut off @ (AM) (PM) Date 1-15-76

Method used 1-15-76 Witnessed by 1-15-76

Remarks: Water 150-375, 434-608, 697-812, 1023-26

Surface 26" hole TD 140' KB Run 6 jts welded 72"

Cmt 210/50 Class C 2% cc 1/4" celloflake PD 10:30 PM Cmt 40/50

1-15-76