

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Mark Fred. Co.</i>		Lease <i>Bredshaw</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980 N 4 E</i>	Section <i>2</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor			Type of Equipment <i>Rotary to start 11-25-76</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>20"</i>	<i>16"</i>	<i>65</i>		<i>200</i>	<i>250 cum.</i>
<i>15"</i>	<i>11 3/4"</i>	<i>42</i>		<i>1350</i>	<i>550 "</i>
<i>11"</i>	<i>8 7/8"</i>	<i>24</i>		<i>2000</i>	<i>450 "</i>
<i>7 7/8"</i>	<i>5 1/2"</i>	<i>20</i>		<i>7200</i>	<i>300</i>

Casing Data:

Surface *30* joints of *11 3/4* inch *42* # Grade *API New 11-40*

(Approved) (~~Rejected~~)

Inspected by *John Williams* date *3-4-77*

Cementing Program

Size of hole *15"* Size of Casing *11 3/4* Sacks cement required *850/sk*

Type of Shoe used *Guide* Float collar used *Insert Btm 2 jts welded Threadlock*

TD of hole *1215' EL* Set *1203' EL* Feet of *11 3/4* Inch *42* # Grade *11-40*

New-used csg. @ *1203' EL* with *150* sacks neat cement around shoe *2000*

+ *200/sax* *Thix-set 106 lbm 30 sec* *500/sk* *Howe-Lite 5" 61 lbm 4" 40 lbm 2" 20 lbm*

Plug down @ *11:30* (AM) (PM) Date *3-6-77*

Cement circulated *Yes* No. of Sacks *50/sk*

Cemented by *Halliburton* Witnessed by *John Williams*

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *1 Cont. 1 Basket 500*

Water: *255-442 - 470-809, 878-915, 1000-14, 1037-42*

(Grant 200-21)