

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TR
(Other instructi
verse side)

CATE
OR re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

ckf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P.O. Box 1933, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & 1684' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3555' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 23417

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Travis Deep

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

South Empire Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 18, T18S, R29E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

PLUG & ABANDON INTENT: TOC @ 4600' by CBL; perfs @ 6360-6552'.

- Set 4 1/2" CIBP @ 6300± w/35' cmt on top.
- Free point 4 1/2". Cut & pull approx. 4000'± 11.6# J-55 4 1/2" csg.
- Pump 100' plug (50' in & out of 4 1/2" cut off).
- Pump 100' plug from 3550 to 3450' (across 8 5/8" shoe).
- Pump 100' plug from 732-632' (base of salt). → As per telecon w/ Ray Nokes; Heyco will cut/pull 8 5/8" csg. @ ± 1900'; spot 100' plug in/out of csg stub. 7/21/87 SJS
- Pump 150' plug from 450 to 300' (across 12 3/4" shoe).
- Pump 50' plug @ surface.
- Install dry hole marker.

RECEIVED
JUL 16 10 50 AM '87
CARLSBAD RESOURCE
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Manager/Engineer

DATE 7-15-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side