

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates Petr Corp</u>		Lease <u>Gulf HI</u>		Well # <u>1</u>	
Location of Well	Unit <u>J</u> <u>16503</u> <u>1750e</u>	Section <u>28</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>Byrd Drilling Co.</u>		Type of Equipment <u>Rotary</u>			

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>9 1/2"</u>	<u>7"</u>	<u>20</u>		<u>1200</u>	<u>air</u>
<u>6 1/4"</u>	<u>4 1/2 + 5 1/2</u>	<u>10.5 + 15.5</u>		<u>1850</u>	<u>175</u>

Casing Data:

Surface 32 joints of 7" inch 20 # Grade API New K-55
(Approved) (~~Rejected~~)

Inspected by Selam Mermis date 2-4-77

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required 500/sx

Type of Shoe used Guide Float collar used None Btm 2 jts ~~welded~~ Thread Lock

TD of hole 1184' KB Set 1170' GL Feet of 7" Inch 20 # Grade K-55

New-used csg. @ 1170' GL with 150 sacks neat cement around shoe Class C 2% cc
+ 350/sx sack Class C Mix additives 6" Gilsomite 1/4" Flocele 2% cc

Plug down @ 8:30 (AM) (PM) Date 2-5-77

Cement circulated Yes No. of Sacks 43/sx

Cemented by Denton Witnessed by Selam Mermis

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last water 637-43