

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

**RECEIVED**  
 NEW MEXICO OIL CONSERVATION COMMISSION  
**FEB 15 1977**

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

**D. C. C.**  
**ARTESIA, OFFICE**

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Gulf "HI"	
9. Well No. 1	
10. Field and Pool, or Wildcat Und. Atoka San Andres	
12. County Eddy	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER <u>J</u> , <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>1750</u> FEET FROM THE <u>East</u> LINE, SECTION <u>28</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3374' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 9½" hole at 3:00 PM 2-2-77.

TD 1184'. Ran 32 joints of 7" 20# K-55 new casing (1185.99') Set at 1184' KB. 1-Guide shoe, 2 centralizers at 1147 and 580', 2 baskets at 544-618'. Cemented by Denton w/350 sacks of Lite (6# gilsonite and 1/4# flocele) 2% CaCl followed w/150 sacks of Class C 2% CaCl. Cement circulated. PD 8:30 AM 2-5-77. WOC 18 hours, nipples up, installed BOP's and tested to 1000#. OK. Reduced hole to 6¼", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geological Secretary DATE 2-12-77  
 APPROVED BY H. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE FEB 15 1977  
 CONDITIONS OF APPROVAL, IF ANY: