

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

FEB 24 1977

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS, C. C.</p> <p align="center"><small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT WELL. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PURPOSES.)</small></p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p>
<p>1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-</p>		<p>5. State Oil & Gas Lease No.</p>
<p>2. Name of Operator Yates Petroleum Corporation</p>		<p>7. Unit Agreement Name</p>
<p>3. Address of Operator 207 South 4th Street - Artesia, NM 88210</p>		<p>8. Farm or Lease Name Mallard "IM"</p>
<p>4. Location of Well UNIT LETTER K , 1650 FEET FROM THE South LINE AND 2310 FEET FROM West 28 18S 26E THE LINE, SECTION TOWNSHIP RANGE NMPM.</p>		<p>9. Well No. 1 2</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 3387' GR</p>		<p>10. Field and Pool, or Wildcat Undesignated</p>
		<p>12. County Eddy</p>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spudded a 9½" hole at 12:30 PM 2-15-77.

TD 1170'. Ran 29 joints of new 7" 20# K-55 ST&C R-3 (1172.56') of casing set at 1170' KB w/1-Guide shoe and insert float. Centralizers at 1135 and 575'. Baskets at 615 and 536'. Cemented by Howco w/300 sacks of Howco Lite, 5# gilsonite, 1/4# flocele 2% CaCl followed w/150 sacks of Class C 2% CaCl. PD 11:50 AM 2-17-77. Circulated estimated 35 sacks to pit. Cement dropped 40' and filled hole w/1½ yards of Ready-Mix. WOC 18 hours, nipples up, installed BOP's, tested to 1000#. OK. Reduced hole to 6½", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 2-24-77

APPROVED BY W. A. Gressitt TITLE SUPERVISOR, DISTRICT II DATE FEB 25 1977

CONDITIONS OF APPROVAL, IF ANY: