

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State ☐ For ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Midwest HH Com
3. Address of Operator 207 So. 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER F, 1980 FEET FROM THE North LINE AND 1980 FEET FROM West THE LINE, SECTION 21 TOWNSHIP 18S RANGE 27E NMPM.		10. Field and Pool, or Wildcat Undes. Strawn
15. Elevation (Show whether DF, RT, GR, etc.) 3345' GR		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Perforate & treat additional Strawn ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103,

Set standing valve in packer at 8758'. Set retrievable bridge plug at 8755', WIH w/casing gun on wireline and perforated 8504'-8524' w/18 - .34" holes as follows: 8504'-8509' (10 holes), 8515-8518' (4 holes), and 8521'-8524' (4 holes). Set tubing in packer at 8470'. Swabbed with no show of oil or gas. Treated perforations 8504'-8524' with 2000 gallons 15% acid and nitrogen. Swabbed load back and stabilized at 30# on 1/4" choke = 85 MCF/D. Loaded hole and pulled packer at 8470' and retrievable bridge plug at 8755'. Reran tubing and packer and set at 8463'. Swabbed well in. Producing from Strawn zones 8504'-8524' and 8807'-8820'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall TITLE Engineer DATE 9/2/80

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE SEP 5 1980

CONDITIONS OF APPROVAL, IF ANY: