

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir  
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Harvey E. Yates Company

3. Address and Telephone No.

P.O. Box 1993 , Roswell, NM 88202 1-505-623-6601

4. Location of Well (Footage, Sec., T., R., M, or Survey Description)

G, 1980' FNL & 1780' FEL  
SEC. 13, T-18S, R-28E

5. Lease Designation and Serial No.

NM-23417

6. If Indian, Allotee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

TRAVIS DEEP UNIT # 2

9. API Well No.

30-015-22117

10. Field and Pool, or Exploratory Area

TRAVIS UPPER PENN

11. County or Parish, State

EDDY CO., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other P&A

☐ Change in Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

CORRECT NAME FOR THIS WELL IS AS STATED ABOVE NOT TRAVIS PENN # 3 AS INC INDICATED.

5-23-95 SET CIBP @ 9045' DUE TO COLLAR @ 9051'+

RAN PIPE INSPECTION LOG. MADE 2 DUMP RUNS AND DUMPED 50' CMT ON TOP CIBP @ 9045'.

NEW PBTD # 8995'.

GIH TO 8225' & SPOT 100' PLUG TO 8125' (TOP OF WOLFCAMP)

CUT 5 1/2" CSG @ 6500' +/- & PULL OUT OF HOLE. (TOC @ 7060' PER TEMP SURVEY)

GIH w/ TBG TO 6550' (OR 50' INSIDE STUB). SPOT 25 SK PLUG 6550-6450'. (TAG)

PULL TBG TO 4600' & SPOT 25 SK PLUG FROM 4600 TO 4500'. (TAG)

PULL TO 3550' & SPOT 25 SK PLUG FROM 3550 TO 3450'. INTERMEDIATE @ 3500'. (TAG)

PULL TBG TO 700' & SPOT 100' PLUG FROM 700 TO 600'.

PULL TBG TO 400' & SPOT 100' PLUG FROM 400 TO 300'. SURFACE @ 360'

PULL TO 50' & SPOT 10 SK PLUG.

INSTALL DRY HOLE MARKER

BACK FILL PIT, CUT OFF ANCHORS, CLEAN LOCATION.

CALL BLM 24 HOURS PRIOR TO COMMENTMENT

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct

Signed

RAY F. NOKES

Title

PROD. MGR./ ENG.

Date

6/4/98

(This space for Federal or State office use)

Approved by

(ORIG. SGD.) ALEXIS C. SWOBODA PETROLEUM ENGINEER

Title

Date

DEC 24 1998

Conditions of approval, if any: