

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIPL
(Other instructions
reverse side)F-
Jr-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 0440087

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "CX"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 7-18S-25E

Unit L NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ JUL 22 1977

2. NAME OF OPERATOR Yates Petroleum Corporation O. C. C.

3. ADDRESS OF OPERATOR ARTESIA, OFFICE
207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 1980' FSL & 660' FWL of Section 7-18S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3646 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 17½" hole at 12 noon 7-12-77. Ran 8 joints of 13-3/8" 61# J-55 (320') of casing set at 320' KB. Cemented w/250 sacks of Class C 4% CaCl 1/4# flocele/sx. (Slurry wt. 14.8, 1.32 cu. ft/sx. Compressive Strength at 70 degrees 1023 psi in 12 hours.). Cement circulated. PD 12 midnite 7-12-77. WOC 12 hours. Baked offlanding joint, reduced hole to 12¼", drilled plug and tested to 600#. OK. Resumed drilling.

TD 1050'. Ran 26 joints of 8-5/8" 24# J-55 LT&C (1052') of casing set at 1050'. 1-Guide shoe, insert float, 1-centralizer at 1010'. Cemented w/400 sacks of Howco Lite 1/4# flocele 2% CaCl/sx tailed in w/100 sacks of Class C 2% CaCl. PD 12:20 AM 7-15-77. Cement circulated 28 sacks to surface. WOC 18 hours, nipples up, installed BOP's, tested to 1500#. OK. Reduced hole to 7-7/8", drilled plug and tested to 600#. OK. Resumed drilling.

RECEIVED

JUL 19 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Geol. Secty

DATE 7-19-77

(This space for Federal or State office use)

APPROVED BY

TITL ACTING DISTRICT ENGINEER

DATE JUL 21 1977

CONDITIONS OF APPROVAL, IF ANY: