

UNITED STATES Artesia, NM 88210

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

c/SF
A & H Engineering

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1980' FSL & 660' FWL, Sec. 7-18S-25E

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐

RECEIVED
FEB 1 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE

NM 0440087

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Federal CX Cam

FEB 24 1982

9. WELL NO.

2

O. C. D.

10. FIELD OR WILDCAT NAME

ARTESIA OFFICE

Eagle Creek Permo Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit L, Sec. 7-18S-25E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3661' KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rigged up. Pulled tubing and packer. WIH and perforated 5095-5101' w/12 .40" holes (2 SPF). Swabbed well. No show of gas. Acidized well with 2500 gallons 15% NE acid and nitrogen plus 8 ball sealers. Flowed well back. Stabilized well at 80 psi on 1/8" choke. Pulled packer and RBP. Ran back in hole with tubing and packer. Set packer at 5060', seating nipple in tailpipe at 6507'. Turned well over to pumper.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Engineering Secty DATE 1-29-82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY

ACCEPTED FOR RECORD
ROGER A. CHAPMAN

FEB 16 1982

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO