

- F. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind.
- G. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations.

8. ANCILLARY FACILITIES.

- A. None required.

9. WELLSITE LAYOUT.

- A. Exhibit D shows the relative location and dimensions of the well pad, the reserve pits, sump pit, etc.
- B. Relatively little leveling will be necessary to construct the location or the new access road. The ground surface at the wellsite is relatively flat, with only very minor anomalies. The pad surface will be covered with at least six inches of compacted caliche.
- C. The reserve pits will be plastic lined.
- D. The pad and pit area has been staked and flagged.

10. PLANS FOR RESTORATION OF THE SURFACE.

- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleaned of all trash and junk to leave the wellsite in as aesthetically pleasing a condition as possible.
- B. Unguarded pits, if any, containing fluids will be fenced until they have been filled.
- C. If the proposed well is non-productive and the site is abandoned, arrangements will be made with the owner of the land at the location for appropriate reclamation of the surface (see attached letter re agreement between the operator and the land owner.) Any applicable regulations of the Bureau of Land Management and United States Geological Survey will be complied with and reclamation will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment.

11. OTHER INFORMATION.

- A. Topography: The land surface is relatively flat, with only very minor anomalies.
- B. The topsoil at the location is moderately soft sand.