

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYNMOCC COPY.
SUBMIT IN TRIPLI
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

0487738

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Rio

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

29-T18S-R25E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

JUN 14 1977

2. NAME OF OPERATOR

Morris R. Antweil

3. ADDRESS OF OPERATOR

Box 2010, Hobbs, New Mexico 88240

O. C. G.
ARTESIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL and 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3581 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Spudded 10:15 AM 1 June 77, Drilled 17-1/2" hole to
TD 300'. Cmtd 13-3/8" 43# casing @ 300' w/325 sx. Class "C"
cement containing 2% CaCl₂. Plug down 6:50 PM 1 June, 1977.
Circulated out 18 sx. spotted 5 yds ready-mix around top of
13-3/8". WOC 18 hrs. Tested casing w/500 psi - 30 mins-OK.
Drilling ahead w/12-1/4" bit.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NMOCC COPY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Copy to 5F
Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. 0487738	
2. NAME OF OPERATOR Morris R. Antweil		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -----	
3. ADDRESS OF OPERATOR Box 2010, Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME -----	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL and 1980' FEL		8. FARM OR LEASE NAME Rio	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3581 GR		10. FIELD AND POOL, OR WILDCAT Undesignated/1104 R.O.W.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 29-T18S-R25E	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 10:15 AM 1 June 77, Drilled 17-1/2" hole to TD 300'. Cmt'd 13-3/8" 48# casing @ 300' w/325 sx. Class "C" cement containing 2% CaCl₂. Plug down 6:50 PM 1 June, 1977. Circulated out 18 sx. spotted 5 yds ready-mix around top of 13-3/8". WOC 18 hrs. Tested casing w/500 psi - 30 mins-OK. Drilling ahead w/12-1/4" bit.

RECEIVED

JUN 10 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 3 June, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE JUN 10 1977

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side