

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

AUG 10 1977

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Humphrey IH
9. Well No. 1 1
10. Field and Pool, or Wildcat Penasco Draw (Yeso S.A.)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER- ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th Street - Artesia, NM, 88210

4. Location of Well
UNIT LETTER 0 330 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 28 TOWNSHIP 18S RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3375' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER Set Prod csg, perf, & treat <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

TD 3100' - Ran 4½" & 5½" casing as follows: Ran 56 joints of 4½" 9.5# J-55 (2154') and 23 joints of 5½" 14# J-55 (946') (Total 3100') set at 3100', 1-Guide shoe and centralizers at 3060, 2795, 2640, 2570, 2520, 2470, 2430, 2390, 2290, 2155, 2100, 1800, 1760, 1660'. Cemented w/265 sacks of Class C cement. PD 5:30 PM 7-23-77. Cement circulated 20 sacks to surface. WOC and tested to 1000#. OK.

TD 3100' - WIH and perforated 2524-2674' w/22 .50" holes as follows: 26, 35, 37, 39, 41, 47, 48 & 62', 2623, 24½, 28, 26½, 58, 60, 61, 64, 67, 68½, 70, 71½ and 74'. Treated w/60000 gallons treated water and 95000# sand, 75000# 20-40 sand and 20000# of 100 mesh w/ball sealers.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christina Tomlinson TITLE Geol. Secty DATE 8-9-77

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE AUG 11 1977

CONDITIONS OF APPROVAL, IF ANY: