

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

INMOCC  
SUBMIT IN THIS  
(Other instructions on  
verse side)

copy to SR  
Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ RECEIVED

2. NAME OF OPERATOR WILLIAM A. & EDWARD R. HUDSON OCT 3 1977

3. ADDRESS OF OPERATOR Box #198, Artesia, New Mexico 88210 D. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface 25' FNL and 330' FEL of Section 25-17S-31E ARTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3909 KB

5. LEASE DESIGNATION AND SERIAL NO.

71-029415-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Puckett "B"

9. WELL NO.

24

10. FIELD AND POOL, OR WILDCAT

Maljamar, G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25-17S-31E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On Sept. 22, 1977, acidized perforations at 3935-50 with 3,000 gals. 20% acid + 5,750 gals. Redifrac gel pad with 4,000# FLA 100 sand. This was below a packer set at 3921'. Had difficulty in breaking formation down at 4,000 psi. Treated at 2-3/4 to 3-1/8 BPM at 2,650 psi. Flowed back load, then flowed back 100% water. Set bridge plug at 3890' and packer at 3809'. Acidized perforations at 3844-64 with 6,000 gals. 20% acid + 10,250 gals. Redifrac gel pad with 8,000# FLA 100 sand. Used 2 stages with 100# Benzoic acid plug between stages. Flowed back load, then flowed 500 BO + 30 BWRD.

RECEIVED  
SEP 26 1977  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph L. Bray

TITLE

Consulting Engineer

DATE

Sept. 26, 1977

(This space for Federal or State office use)

APPROVED BY

Joe D. Lora

TITLE

ACTING DISTRICT ENGINEER

DATE

SEP 29 1977

CONDITIONS OF APPROVAL, IF ANY:

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.