

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gata Petr Corp.</i>		Lease <i>Ferguson 1F</i>		Well # <i>1</i>	
Location of Well	Unit <i>3305 2310 W</i>	Section <i>28</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Byrd & Co</i>		Type of Equipment <i>app. 7-20-77 Rotary to start soon as approved</i>			
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>9 3/8"</i>	<i>7"</i>	<i>20</i>		<i>1200</i>	<i>550 air</i>
<i>6 1/4"</i>	<i>4 1/2 x 5 1/2</i>	<i>9.5 + 14</i>		<i>3100</i>	<i>175 air</i>
Casing Data:					
Surface <i>32</i> joints of <i>7"</i> inch <i>20</i> # Grade <i>New & Used J-55 57.0</i>					
(Approved) (Rejected)					
Inspected by <i>Selan Merriam</i> date <i>7-27-77</i>					
Cementing Program					
Size of hole <i>9 3/8"</i> Size of Casing <i>7"</i> Sacks cement required <i>550/54</i>					
Type of Shoe used <i>Guide</i> Float collar used <i>New</i> Btm <i>2</i> jts used <i>Thread back</i>					
TD of hole <i>1160' KB</i> Set <i>1146' GL</i> Feet of <i>7"</i> Inch <i>20</i> # Grade <i>J-55</i>					
New-used csg. @ <i>1146' GL</i> with <i>200</i> sacks neat cement around shoe <i>Class C 2 1/2 cc</i>					
+ <i>350/sax Class C mix</i> additives <i>2 1/2 cc</i>					
Plug down @ <i>5:45 (AM) (PM)</i> Date <i>7-27-77</i>					
Cement circulated <i>Yes</i> No. of Sacks <i>253/54</i>					
Cemented by <i>Denton</i> Witnessed by <i>Selan Merriam</i>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <i>Water 100-349 - 371-547, 565-71, 731-36</i>					