

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>RC Bennett + JC Ryan</u>		Lease <u>Lone Tree</u>		Well # <u>1</u>	
Location of Well	Unit <u>C</u> <u>660W</u> <u>1980W</u>	Section <u>32</u>	Township <u>18</u>	Range <u>25</u>	County <u>Edley</u>
Drilling Contractor <u>McVay Drilling Co.</u>			Type of Equipment <u>Rotary to Start approx 8-5-77</u>		

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48</u>		<u>300</u>	<u>315 circ.</u>
<u>12 1/4</u>	<u>8 7/8</u>	<u>24</u>		<u>1140</u>	<u>150 circ.</u>
<u>7 7/8</u>	<u>4 1/2</u>			<u>9000</u>	<u>400 3x</u>

Casing Data:

Surface 18 joints of 8 5/8 inch 24 # Grade K-55

☒ (Approved) ☐ (Rejected)

Inspected by MW date 8/10/77

Cementing Program

Size of hole 12 1/4" 930 Size of Casing 8 5/8 Sacks cement required 750

Type of Shoe used Hawco Float collar used Insert Btm 3 jts welded Yes

TD of hole 1140 Set 1173 Feet of 8 5/8 Inch 24 # Grade K-55

New used csg. @ 1140 with 200 sacks neat cement around shoe w/ 270 cc
+ 450 sack Hawco Lite w/ 5 # 6.1 + 1/4 # Flo Seal additives + 100 sack Thick Set w/ 5 # 6.1 + 1/4 # Flo Seal

Plug down @ 12:40 (AM) (PM) Date 8/12/77

Cement circulated Yes No. of Sacks 120

Cemented by Hell Burton Witnessed by MW

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Break @ 790'

Baskets @ 711' + 509' Centralizers on 1st + 2nd collar