

Copy to 57.

5-USGS-ARTESIA

1-R. J. STARRAK-15TH FLOC FULSA

NMOCC COPY

1-A.B. CARY-MIDLAND

Form 9-331

(May 1963) 1-FILE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029419-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

LTR. E, 1860' FNL and 660' FWL, SEC. 27

7. UNIT AGREEMENT NAME

SKELLY UNIT

8. FARM OR LEASE NAME

SKELLY UNIT

9. WELL NO.

134

10. FIELD AND POOL, OR WILDCAT

FREN-7-RIVERS

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 27, T-17-S, R-31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3808' GR

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

La Rue Drilling Company spudded 11" hole at 3:30 P.M. 12-3-77.

Drilled to 679'.

On 12-4-77 set 8-5/8" k-55 8rd R3 24" ST&C casing at 679'.

Howco cemented casing w/150 sks. Hal Lite w/6# salt & 1/4# Flocele/sk., and 150 sks. Howco Class "C" Cement w/2% CaCl₂. Total Cement 300 sacks.

Cement Circulated.

WOC - 18 Hours.

Tested casing to 1200# for 30 Minutes.

No drop in pressure.

RECEIVED

FEB 6 1978

O. C. C.
ARTESIA, OFFICE

RECEIVED
FEB 2 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE

AREA SUPERINTENDENT

DATE

JANUARY 31, 1978

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

/bh

*See Instructions on Reverse Side