

5-USGS-ARTESIA

1-R.J. STARRAK-15TH FLOOR LSA

NMOCG COPY

Copy to 57

1-A.B. CARY-MIDLAND

Form 9-331

(May 1963) 1-FILE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029419-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

LTR. E, 1860' FNL AND 660' FWL, SECTION 27

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3803' GR

7. UNIT AGREEMENT NAME

SKELLY UNIT

8. FARM OR LEASE NAME

SKELLY UNIT

9. WELL NO.

134

10. FIELD AND POOL, OR WILDCAT

FREN 7-RIVERS

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 27-T-17-S, R-31-E

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

XX

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 2650'.

On 12-8-77 set 5-1/2" 14# 8rd H-40 ST&C casing at 2650'.

Howco cemented with 700 sks. Hal Lite w/6# salt and 1/4# Flocele/Sk. and
200 sks. Calss "C" Cement w/2% CaCl₂. Total cement - 900 Sacks.

Cement Circulated.

WOC - 24 Hours.

Tested casing with 1200# for 30 Minutes.

No drop in pressure.

RECEIVED
FEB 2 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

FEB 6 1978

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE

AREA SUPERINTENDENT

DATE

JANUARY 31, 1978

(This space for Federal or State office use)

APPROVED BY

TITLE

DISTRICT ENGINEER

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

/hh