

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Marathon Energy Corp.</i>		Lease <i>Johnny</i>		Well # <i>1</i>	
Location of Well	Unit <i>330 S 1650 E</i>	Section <i>35</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Pennsylvania Pulp Co.</i>			Type of Equipment <i>Rotary Lariat 8-29-77</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>10"</i>	<i>7"</i>	<i>20</i>		<i>700</i>	<i>Cir.</i>
<i>6 1/4"</i>	<i>4 1/2</i>	<i>10.5</i>		<i>1200</i>	<i>250 SX</i>

Casing Data:

Surface *17* joints of *7"* inch *20* # Grade *API New K-55*
(Approved) (Rejected)

Inspected by *Selan Meemis* date *9-4-77*

Cementing Program

Size of hole *9 1/2"* Size of Casing *7"* Sacks cement required *230/SX*

Type of Shoe used *Guide* Float collar used *Insert* Btm *2* jts *welded* *Thread-Lock*

TD of hole *700' GL* Set *700' GL* Feet of *7" Inch* *20* # Grade *K-55*

New-used csg. @ *700' GL* with *100/SX* sacks neat cement around shoe *Nice 22cc*
+ *130* /sax *Horse Lite* additives *5" C. 1/2 in. 1/4" Floc 2 1/2 cc*

Plug down @ *4:30 (AM)* (PM) Date *9-4-77*

Cement circulated *Yes* No. of Sacks *230/SX*

Cemented by *Halliburton* Witnessed by *Selan Meemis*

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: