

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

SEP 26 1977

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Gulf Oil Corporation	5. State Oil & Gas Lease No. L-423
3. Address of Operator Box 670, Hobbs, New Mexico 88240	7. Unit Agreement Name
4. Location of Well UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 19 TOWNSHIP 18-S RANGE 25-E N.M.P.M.	8. Farm or Lease Name Eddy "GK" State Com
15. Elevation (Show whether DF, RT, GR, etc.) 3624' GL	9. Well No. 1
	10. Field and Pool, or Wildcat Undes. Morrow
	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Completed 12-1/4" hole at 1200' at 11:45 AM, September 19, 1977. Ran 29 joints and 1 cut joint, 1186' of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 1200' with 300 sacks of thickset with 2% Ca C12 and 10# gilsonite and 1/4# flocele per sack, 870 sacks of Howco lite with 2% Ca C12 and 1/4# flocele per sack and 400 sacks of Class C with .5% CFR-2. WOC 6 hours. Temperature survey indicated TOC at 780'. Cemented thru 1" pipe with a total of 885 sacks of cement. Cement circulated. WOC over 24 hours. Tested casing with 1,000#, 30 minutes, OK.

Started drilling 7-7/8" hole at 1200' at 3:15 PM, September 22, 1977.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. B. Sikes, Jr. TITLE Area Engineer DATE September 23, 1977

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE SEP 27 1977

CONDITIONS OF APPROVAL, IF ANY