

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

SEP 1 1977

30-015-22284

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease	STATE ☐	FEED ☒
5. State Oil & Gas Lease No.		

APPLICATION FOR PERMIT TO DRILL, DEEPEN OR PLUG BACK

1a. Type of Work				7. Unit Agreement Name	
b. Type of Well OIL WELL ☒ GAS WELL ☐ OTHER ☐				Ballard Grayburg San Andres Unit	
2. Name of Operator Anadarko Production Company				8. Firm or Lease Name Tract No. 24	
3. Address of Operator P. O. Box 67, Loco Hills, New Mexico 88255				9. Well No. 2	
4. Location of Well UNIT LETTER P LOCATED 660 FEET FROM THE South LINE 990 FEET FROM THE East LINE OF SEC. 5 TWP. 18S RGE. 29E				10. Field and Pool, or Wildcat Loco Hills Queen Grayburg San Andres	
				12. County Eddy	
19. Proposed Depth 2850'		19A. Formation Grayburg		20. Rotary or C.T. Rotary	
21. Elevations (Show whether DT, RT, etc.) 3522' GR		21A. Kind & Status Plug. Bond Blanket		22. Approx. Date Work will start 11-10-77	

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12 1/2"	8 5/8"	24#	350'	150	100
7 7/8"	4 1/2"	10.5#	2,850'	400	2,000

1. Rig up rotary tools.
2. Drill to approximately 350', set and cement 8 5/8" casing, install & test Series 900 double ram hydraulic blowout preventor.
3. Drill to T. D. 2850', set and cement 4 1/2" casing on T. D.
4. Run cased hole logs.
5. Perforate, acidize and frac Grayburg Zones.
6. Install pumping equipment and place well on production.

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,

EXPIRES 12-2-77

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Original Signed by
Jerry E. Buckles Title Area Supervisor Date August 30, 1977

(This space for State Use)

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE SEP 2 1977

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to
surface behind 8 5/8" casing