NO. OF COPIES RECEIVED	3					·
DISTRIBUTION			RECEIV	\mathcal{L}		Form C-103 Supersedes Old
SANTA FE		NE	W MEXICO OIL CON		OMUSSION	C-102 and C-103
FILE					OMMISSION	Effective 1-1-65
U.S.G.S.			OCT 4 TP	<i>.</i> .		Sa. Indicate Type of Lease
LAND OFFICE						State Fco X
OPERATOR			O. C. C.			5. State Oll & Gas Lease No.
	<u> </u>		ARTEBIA, OFF			
OO NOT USE THIS FO	SUNDR	Y NOTICES	AND REPORTS O	N WELLS	ENT RESERVOIR.	
1. OIL X GAS WELL WELL	. 🗆	OTHER-	· ·			7. Unit Agreement Name
2. Name of Operator			V			8, Farm or Lease Name
Yates Petrole	um Cor	poratio	n j			Nickson "BM"
3. Address of Operator			1		·····	9. Well No.
207 South 4th	Stree	t - Art	esia, NM ·88	1210		1 = 4
4. Location of Well						10. Field and Pool, or Wildcat
UNIT LETTER	16	50	FROM THE South	LINE AND	330	Penasco Draw(S.A.Yeso
THE West	INE, SECTIO	<u>я <u>30 </u></u>	TOWNSHIP 18	IS RANGE	26E	
			Elevation (Show whethe			
	12. County					
	$\overline{\Pi}$		3445' GR			Eddy
16.	Check A	<i>ippropriate</i>	Box To Indicate	Nature of Not	tice. Report or	Other Data
NOTIC	ENT REPORT OF:					
PERFORM REMEDIAL WORK]		PLUG AND ABANDON	REMEDIAL WOR	к 🗌	ALTERING CASING
TEMPORARILY ABANDON]			COMMENCE DRI	LLING OPNS. X	PLUG AND ABANDONMENT
PULL OR ALTER CASING]	•	CHANGE PLANS	CASING TEST A	ND CEMENT JOB	
				OTHER		
OTHER			·][
12 December 12 C			2			
work) SEF RULF 1103.	infrated Ob	signons (Clear	ty state all pertinent de	class, and give pe	ertinent dates, inclu	iding estimated date of starting any proposed

Spudded a 15" hole at 2:30 PM 9-14-77.

<u>TD 437'</u> - Ran 10 joints of 10-3/4" 40# J-55 casing (437') set at 437', 1-float collar. Cemented w/300 sacks of Class C 4% CaCl. Slurry wt. 14.8, 1.32 cu. ft. per sack. Compressive Strength at 70 deg 1023 psi in 12 hours. Cement circulated 20 sacks to surface. PD 5:30 AM 9-15-77. WOC 12 hours cut off, reduced hole to $9\frac{1}{2}"$, drilled plug and tested to 600# \acute{O} K, resumed drilling. <u>TD 1127'</u> - Ran 28 joints of 7" 20# J-55 casing (1129') set at 1127'. 1-Guide Shoe, 2-centralizers and baskets at 885 and 442'. Cemented w/250 sacks of Denton Lite 2% CaCl followed w/150 sacks of Class C 2% CaCl. PD 10:30 AM 9-18-77. Cement circulated 5 sacks to surface. WOC and cement fell back, filled hole to surface w/1 $\frac{1}{2}$ yards of Ready-Mix. WOC 18 hours, cut off, NU tested BOP's to 1000#. OK. Reduced hole to $6\frac{1}{4}"$, drilled plug and tested to 600# OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the b	Geol. Secty	DATE_	9-29-77	
APPROVED BY WALL IF ANY:	SUPERVISOR, DISTRICT II	DATE_	OCT 5 1977	