

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Copy to SF
Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. LC-050906	
2. NAME OF OPERATOR DEPCO, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 800 Central, Odessa, Texas 79761		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit Letter G, 1980 FN & EL, 8-18-29		8. FARM OR LEASE NAME Welch Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3515 GR.		10. FIELD AND POOL, OR WILDCAT Empire Morrow, South	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 8-18a-29a	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mex.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Commencement	☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-6-77 Spud 8:00 A.M. Drilled 17 1/2" hole to 400'. Ran 13 3/8" 48# H-40 casing set at 400'. Cemented w/280 sks. 50-50 Permox, 2% gel, 5# Gilsomite, 1/4# Calo Flakes & 2% ca cl. Followed w/150 sks. Class "C" w/2% ca cl. Cement circulated. WOC 18 hrs., tested casing at 1000# for 30 minutes. Held OK.

10-11-77 Drilled 11" hole to 2900'. Ran 12 jts. (483.71') 8 5/8" 32# J-55 casing, 55 jts. (2205.28') 8 5/8" 24# J-55 casing, 5 jts. (211.01') 8 5/8" 32# J-55 casing. Cemented w/1100 sks. Class "C", 2% Lodense, 5# Gilsomite, 1/4# Calo Flakes & 2% ca cl. Followed w/200 sks. Class "C" w/2% ca cl. WOC 18 hrs. Tested casing @ 1000# for 30 minutes. Held OK.

RECEIVED
OCT 19 1977
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED D. R. Mason D. R. Mason TITLE Chief Clerk DATE 10-18-77

(This space for Federal or State office use)

APPROVED BY Lee D. Lara TITLE ACTING DISTRICT ENGINEER DATE OCT 20 1977

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.