

NMOC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP. DATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-A-3302

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

M. Brad Bennett, Inc. & Robert K. Hillin

3. ADDRESS OF OPERATOR

P.O. Box 2062, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

990' FSL & 2310' FEL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

King-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat *Review*

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 5-T-18-S R-23-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) Plug & Abandon

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 17 1/2" Hole to 156' and cemented 13 3/8" O.D. 61#, new csg with 150 sx. Class "C" w/2% CaCl/sx, cement circulated 10/1/77.

Drilled 12 1/4" hole to 1505' and cemented 8 5/8" O.D. 24#, new csg. with 200 sx. Hall. thix-set, 225 sx. Hall. Light, 300 sx. Class "C". Ran 1" down annulus and cemented with total of 235, cement to surface. Test B.O.P. to 3000#. Held O.K.

Drilled to total depth 7600'. Ran FDC-CNL-GR and dual laterolog-GR. 10/27/77 plugged and abandoned. Set cement plugs as follows: 50 sx. (6680'-6530'), 35 sx. (5100'-5000'), 35 sx. (3520'-3420'), 40 sx (1550'-1450'), 10 sx plug (25'-surface). Install dry hole maker. Between plugs is mud with 8.9#/gal wt.

NOTE: Verbal plugging approval was received from Mr. Knolph, 10/25/77, and well was plugged while rig was on location.

RECEIVED

NOV 8 1977

18. I hereby certify that the foregoing is true and correct

SIGNED *M. Brad Bennett*

TITLE Petroleum Engineer

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

(This space for Federal or State office use)

APPROVED BY *Lee S. Lara*
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE OCT 25 1978