

N.M.O.C.D. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved,
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-A-3302

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Moisa LG Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Woodcock

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 5-18S-23E
Unit O NMPM

12. COUNTY OR PARISH

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a well in a different Federal or State.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER

RE-ENTRY

AUG 31 1979

2. NAME OF OPERATOR

Yates Petroleum Corporation

O.C.C.

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

990' FSL & 2310' FEL of Section 5-18S-23E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3992' CR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud COTD, Set Prod Csg.

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was drilled to a total depth of 7600' by M. Brad Bennett, Inc. & P&A, 10-27-77. Yates re-entered this well and cleaned out to a TD of 4590'. Moved in 55 Well Service - Reverse Unit, removed dry hole marker, installed BOP's and started cleanout at 6:16 PM 7-23-79. Drilled all plugs and cleaned out to 4590. Ran 113 joints of 5½" 14# J-55 (4557') of casing set at 4548'. 1-Guide shoe at 4548' and float collar at 4519'. Cemented w/160 sacks of 50/50 Poz Class C 1/4#/ sack flocele, 5#/sack gilsonite, 5#/sack salt. PD 3:20 PM 7-27-79. WOC and tested to 1000# OK.

RECEIVED

AUG 29 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct:

SIGNED Lustine J. J. J. TITLE

Geol. Secty.

DATE 8-29-79

(This space for Federal or State office use)

APPROVED BY George H. Stewart TITLE

ACTING DISTRICT ENGINEER

DATE AUG 30 1979

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side