

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-3302A A-3302

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Moisa LG Federal #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Wildcat

11. County or Parish, State

Eddy Co., NM

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other P & A

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 2310' FEL of Section 5-T18S-R23E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging operations began on July 23, 1993. Plugged well as follows:

1. Set 5-1/2" CIBP at 4135'. Circulated casing with 95 barrels 10# mud.
2. Spotted a 25 sacks cement (Class "C") plug from 4135-3883'.
3. Jet cut 5-1/2" casing at 3540'. POOH with casing.
4. Spot a 65 sack cement plug inside casing stub from 3620-3325'. WOC and tag plug at 3402'.
5. Spot a 40 sack cement plug from 1937-1781'.
6. Spot a 40 sack cement plug from 1563-1412'. WOC and tag cement at 1438'.
7. Spot a 25 sack cement plug from 95' to surface.
8. Cut off wellhead and installed regulation abandonment marker. PLUGGED AND ABANDONED. PLUGGING COMPLETED JULY 28, 1993.

Approved as to plugging of the well bore,
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Rusty Klein

Title Production Clerk

Date August 28, 1993

(This space for Federal or State office use)

(ORIG. SGD.) JOE G. LARA

Approved by
Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date 9/23/93

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side