

NMOCC COPY

Form 9-331  
(May 1965)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-9542-S

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FNL &amp; 1980' FEL, Section 5, T-18-S, R-25-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3602' GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Grynberg "A" Federal

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

Field and Pool, Etoka

Under Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 5, T-18-S, R-25-E

12. COUNTY OR PARISH

13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒  
☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Commence drilling

☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.) \*

McVay Drilling Co. spudded 17 1/2" hole at 11:30 AM 10-21-77. Reached TD of 17 1/2" hole at 300' at 4:30 PM 10-21-77. Ran 7 jts and 1 cut jt 13 3/8" 48# H-40 ST & C 8 Rd casing (286'). Set at 300'. Cemented with 300 sacks Class C with 4% CaCl2. Cement circulated. WOC 18 hours. Tested casing 500 psi for 30 min - OK.

Started drilling 12 1/4" hole at 300' at 4:00 AM 10-22-77. Reached TD of 12 1/4" hole at 1200' at 2:15 PM 10-23-77. Ran 28 jts and 1 cut jt 8 5/8" 24# K-55 ST & C casing (1184'). Set at 1200'. Cemented with 300 sacks Thickset with 10# Gilsonite, 1/4# flocele, 2% CaCl2, 400 sacks Howco lite with 10# Gilsonite, 1/4# flocele, 200 sacks Class C with 2% CaCl2. Cement circulated. WOC 18 hours. Tested casing to 2500# for 30 min - OK.

Started drilling 7 7/8" hole at 1200' at 3:15 AM 10-25-77.

18. I hereby certify that the foregoing is true and correct

SIGNED

N. B. Sikes, Jr.

TITLE Area Engineer

(This space for Federal or State office use)

APPROVED BY

Lee A. Lora

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACTING DISTRICT ENGINEER

DATE

OCT 26 1977

RECEIVED  
OCT 26 1977  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO  
DATE 10-25-77

\*See Instructions on Reverse Side