

NMOCC COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-9542-S

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Grynberg "A" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Richard Morrow  
Undes Morrow11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 5, T-18-S, R-25-E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

RECEIVED

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations.  
See also space 17 below.)  
At surfaceDEC 16 1977  
A.C.C.  
ARTESIA, OFFICE

660' FNL and 1980' FEL, Sec 5, T-18-S, R-25-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3602' GL

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

5 1/2" casing

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Reached TD of 7 7/8" hole at 8400' at 12:15 PM 11-10-77. Ran 201 jts and 1 cut jt 5 1/2" 17# (2457') and 15.50# (5958') K-55 LT & C casing set at 8400'. Cemented with 550 sacks Class H with 5# HCL per sack and .75% CFR-2. WOC 6 hr. TSITOC 6400'. WOC over 24 hours. Tested 5 1/2" casing to 3000# for 30 min OK.

Installed valves above ground level on all casing strings; approved by Bill Grisset OCC Artesia. Filled Cellar.

RECEIVED

DEC 13 1977

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Engineer

DATE

12-9-77

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

DEC 15 1977

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side