

Form 5-331  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-9542-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Grynberg "A" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Cisco

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 5-T18S-R25E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. NAME OF OPERATOR

Gulf Oil Corporation

ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

660' FNL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3602' GL

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF


PULL OR ALTER CASING


FRACURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF


REPAIRING WELL


FRACURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

P&A Strawn, Perfd, Aczd

X

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

POH with production equipment. Set CIBP at 7500', cap with 35' cement. Perf 6485-90', 6512-19', 6550-55', 6573-78' & 6595-6600' with (1) 1/2" burrless decentra-  
lized o-phase JHPF (25 holes). Acidize with 6000 gals 15% NEFE slick with (6) 7/8" RCNB's. Flush with KCL water. Max pres 7200#, avg 6500#, min 5200#, avg inj rate 4.8 BPM, ISIP 3600#, 15 min 2200#. Now WO production equipment.

RECEIVED

NOV 6 1980

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*RD Pitter*

TITLE

Area Engineer

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

11-5-80

NOV 10 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO