

NEW MEXICO OIL CONSERVATION COMMISSION

DRAWER DD

ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr Corp.</i>		Lease <i>White 14</i>		Well # <i>1</i>	
Location of Well	Unit <i>16505 330e</i>	Section <i>28</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Verna Drilling Co</i>		Type of Equipment <i>Rotary to start 10-21-77</i>			

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
9 1/2"	7	20		1150	500 ccs
6 1/4"	4 1/2 x 5 1/2	10.5 + 15.4		2900	225 "

Casing Data:

Surface 29 joints of 7" inch 20 # Grade API New J-55 STC
(Approved) (Rejected)

Inspected by Delan Meemio date 10-24-77

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required 400/sx

Type of Shoe used Guide Float collar used Insert Btm 2 jts ~~welded~~ Thread Lock

TD of hole 1125'KG Set 1112'GL Feet of 7" Inch 20 # Grade J-55

New-used csg. @ 1112'GL with 150/ sacks neat cement around shoe Class C 5%cc
+ 250/ sax Class C Lite additives 5# Gilsomite 1/4 Celloflake 2%cc

Plug down @ 5:00 (AM) (PM) Date 10-24-77

Cement circulated No No. of Sacks None

Cemented by Deitain Witnessed by Delan Meemio

Temp. Survey ran @ 11:15(AM) (PM) Date 10-24-77 top cement @ 370

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Ran 1" to 350' Taged at 150/sx Class C 4%cc PD 1:15 PM

Possible water 115-42, 150-210, 220-77, 312-421, 305-67

640-50, 885-88