

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name White "IU"
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	9. Well No. 1 1
4. Location of Well UNIT LETTER I, 1650 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 28 TOWNSHIP 18S RANGE 26E NMPM.	10. Field and Pool, or Wildcat Und. Yeso
15. Elevation (Show whether DF, RT, GR, etc.) 3360' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 9½" hole at 5:15 PM 10-21-77.

TD 1125'. Ran 29 joints of 7" 20# J-55 casing (1126') set at 1125'. 1-Guide Shoe, 2-Centralizers and 2 Baskets at 829-281'. Cemented w/250 sacks of Denton Lite 2% CaCl followed w/150 sacks of Class C 2% CaCL. Cement did not circulate. PD 5:10 AM 10-24-77. WOC 6 hours. Ran Temperature Survey and found top of cement at 370'. Ran 1" and tagged cement at 350', spotted 150 sacks of Class C 4% CaCl. PD 1:15 PM 10-24-77. Cement circulated 10 sacks to surface. WOC and cement fell, filled hole with 1½ yards of Ready-mix. WOC 18 hours, NU, tested BOPs to 1000#. OK. Reduced hole to 6-1/8", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine L. Anderson TITLE Geol. Secty. DATE 10-28-77

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE NOV 1 1977

CONDITIONS OF APPROVAL, IF ANY: